

1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-13-1644-005
Product Type **Metalic Floor Finish**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

INGREDIENTS	Conc % W/W
Acrylic polymer ULTRA K	30 - 60
2-(2-Methoxyethoxy) ethanol	1 - 5

3. Hazards Identification

www.rxmarine.com

N/A

4. First Aid Measures

www.rxmarine.com

FIRST AIDS

Contact with Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Occasionally lifting upper and lower lids. Get medical attention at once.
Contact with skin	It should be rinsed off with water.
Ingestion	If this product is swallowed, do not induce vomiting. If victim is conscious give plenty of water to drink. Get medical attention at once. (ANTIPOISON CENTER: 1-800-463-5060)
Inhalation	Move exposed person to fresh air. If irritation persists. Get medical attention promptly.

5. Fire-fighting Measures

www.rxmarine.com

Flammable Condition	Nothing	No
Extinction	Chemical foam, carbon dioxide,	
Flash Point (open cup)	water Superior at 95° C	
Auto-inflammation temperature	N/D	
Dangerous product made by combustion	Carbon oxide	

6. Accidental Release Measures

www.rxmarine.com

Eyes Protection

Respiratory Protection

Skin Protection

Technical installation

Measures if a leaks and spills

Elimination

Protectives Googles.

You don't need a safety mask with normal using.

Protectives cloths, Boots, Googles.

Put good ventilation for close chamber for eliminate a vapour could b

Take off the leaks and put in a identify drums

Rinse the floor with water

Conform with federal and provincial laws Put in a closed material. Pr
freeze

7. Handling and Storage

www.rxmarine.com

N/A

8. Exposure controls and personal protection

www.rxmarine.com

N/A

9. Physical and chemical properties

www.rxmarine.com

Physical State

White Liquid

boiling Point

> 100°C

Odor

Light Acrylic odor

pH

8.5± 0.5

Freezing Point

0°C

% Volatile

N/D

Density (20°C)

1.034 g/cc

Vapor Pressure

N/D

Water solubility

yes

Vapor Density

N/D

10. Stability and reactivity

www.rxmarine.com

Chemical stability

Stable

Incompatibility with other products

Strong oxidizer, strong oxidizer and acid products

Conditions

NO

Polymerisation

None

Decomposition product

Carbon oxide

11. Toxicological information

www.rxmarine.com

Exposition limit

N/D

Absorption way

Inhalation () Eyes (X) Skin () Ingestion (X)

Chronics exposure with the product

NO

Inhalation

No Object

Eyes

Irritation.

Skin

Should be irritating if the product is apply directly on skin

Ingestion

Irritation, nausea

Carcinogenicity

None

12. Ecological informationwww.rxmarine.com

N/A

13. Disposal considerationswww.rxmarine.com

N/A

14. Transport informationwww.rxmarine.com

N/A

15. Regulatory informationwww.rxmarine.com

N/A

16. Other informationwww.rxmarine.com

N/A

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.