

## 1. Product and Company Identification

www.rxmarine.com

Product Name **Dry Cleaning Compound**

Product Type **RXSOL-41-8678-025**

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333/ 5555 / 9999 / 27611360 / 27815540

Fax +91 22 2781 1318/9322594669

Email [mail@rxmarine.com](mailto:mail@rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Hazardous Ingredient	CAS	OSHA PEL	OSHA HAZARD
Odorless Mineral Spirits	64742-48-9	N/E	Acute

## 3. Hazards Identification

www.rxmarine.com

### Emergency Overview

**Appearance:** Clear Liquid      **Odor:** Citrus Scent      **Flashpoint:** 120°F

**Hazard:** Flammable liquid.

**Eye Contact:** May cause temporary eye irritation; injury to eye tissue unlikely

**Skin Contact:** Frequent or prolonged contact may cause temporary irritation. Skin contact may aggravate an existing dermatitis condition.

**Inhalation:** High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, drowsiness, and other central nervous system effects.

**Ingestion:** Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.

**HMIS Hazard Rating:** Health 1 Flammability 2 Reactivity 0

## 4. First Aid Measures

www.rxmarine.com

**Eye Contact:** Immediately irrigate with flowing water continuously for 15 minutes. If irritation persists consult medical personnel.

**Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.

**Inhalation:** Move to fresh air. If irritation persists consult medical personnel.

**Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

Flashpoint: 120°F (closed cup) Upper Flammable Limit (% by volume): 9.8%

Autoignition Temperature: 660°F Lower Flammable Limit (% by volume): 1.3%

General Hazard: Flammable liquid.

Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

Hazardous Decomposition Products: During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to carbon dioxide and carbon monoxide.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Keep all unnecessary personnel away. Eliminate sources of ignition. Prevent additional discharge of material. Prevent material from entering sewers, watercourses, or low areas. Contain and absorb spilled material with sand or earth. Do not use combustible materials such as sawdust. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline products and ignition sources. Cloths used to apply or absorb product should be rinsed with water and stored in a fire-resistant container. Avoid contact with skin and eyes. Use in a well-ventilated area; do not breathe vapors. Wash hands thoroughly after handling.

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

**Engineering Controls:** Normal room ventilation is satisfactory for limited use; keep away from heat and flame.

---

**Eye Protection:** Safety glasses

**Skin Protection:** Use gloves impervious to this material when prolonged or frequently repeated contact could occur.

**Respiratory:** Where concentrations in air may exceed the limits given in Section 2 and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/OSHA approved respirators may be necessary to prevent overexposure by inhalation.

**Exposure guidelines:** N/E

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

Appearance/Physical State:	Clear Liquid	Odor:	Clear scent
Vapor Pressure:	1 mmHg @ 68°F	Vapor Density:	ND
Boiling Point:	354-372°F	Freezing Point:	