

1. Product and Company Identification

www.rxmarine.com

Product Name Professional Heavy Duty Coating Stripper
Product Type RXSOL-41-8897-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax +91 22 2781 1318 :::AOH :0091 9322594669
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Components

Material	CAS Number	%
Dimethyl Adipate	627-93-0	3-7
Dimethyl Succinate	106-65-0	5-10
Dimethyl Glutarate	1119-40-0	10-30
Triethyl Phosphate	78-40-0	3-7
Mineral Powder		1-5
Proprietary Polymer		1-5
Water	7732-18-5	60-80

3. Hazards Identification

www.rxmarine.com

Potential Health Effects :

Eye contact may cause eye irritation with discomfort, tearing, or blurring of vision. Skin contact may cause mild skin irritation. May cause irritation to mouth and digestive tract if ingested. Inhalation may cause irritation of the upper respiratory passages, with coughing and discomfort. Some individuals have experienced blurry vision with prolonged inhalation exposure or skin contact to dibasic esters. Based on observed effects from animal studies, some symptoms of pre-existing eye disease could be aggravated by prolonged exposure to this material.

Carcinogenicity Information :

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

4. First Aid Measures

www.rxmarine.com

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

5. Fire-fighting Measures

www.rxmarine.com

Flammable Properties

Flash Point : >200 F (>93 C)

Method : Pensky-Martens Closed Cup - PMCC.

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

6. Accidental Release Measures

www.rxmarine.com

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up. Initial Containment Dike spill. Prevent material from entering sewers, waterways, or low areas.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material.

7. Handling and Storage

www.rxmarine.com

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.

Handling (Physical Aspects)

Keep container tightly closed.

Do not spray.

Storage

Store between 46-104 F (8-40 C). Do NOT expose to direct sunlight.

Do not allow product to freeze.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Controls

Use only with adequate ventilation.

Do not spray.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses. Where splash potential exists, wear chemical splash goggles.

RESPIRATORS

Wear NIOSH approved respiratory protection, as appropriate.

PROTECTIVE CLOTHING

Where there is potential for skin contact have available and wear as appropriate impervious gloves, apron, pants and jacket.

Exposure Guidelines

Exposure Limits:

DuPont(TM) StoneTech(R) Professional Heavy Duty Coating Stripper

PEL (OSHA) : None Established

TLV (ACGIH) : None Established

Exposure Guideline:

Comments Dibasic: esters DuPont AEL 1.5 ppm (10 mg/m³) 8- and 12-hr TWA

9. Physical and chemical properties

www.rxmarine.com

Boiling Point	~100 C
% Volatile	97%
Solubility in Water	Complete
pH	7
Odor	Slight Almond
Form	Viscous Liquid
Color	Creamy White
Specific Gravity	1.10

10. Stability and reactivity

www.rxmarine.com

Chemical Stability

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

Incompatible with oxidizing agents and strong mineral acids.

Decomposition

Decomposes with heat. Hazardous gases or vapors can be released, including carbon dioxide, carbon monoxide.

Polymerization

Polymerization will not occur.

11. Toxicological information

www.rxmarine.com

Animal Data

The following information is based on toxicology tests conducted with a mixture of dibasic esters similar to the ratios present in this product: dimethyl glutarate 66%,

dimethyl adipate 17%, and dimethyl succinate 17%.

Inhalation 4-hr LC50: > 11 mg/L in rats

Inhalation 1-hr LC50: > 10.7 mg/L in rats

Dermal LD50: > 2250 mg/kg in rabbits

Oral LD50 : 8191 mg/kg in rats

The mixture is a moderate eye and skin irritant in rabbits, but is not a skin sensitizer in guinea pigs. Toxic effects described in rats from exposure by inhalation include respiratory tract irritation. In the first of two 90-day inhalation studies, rats exposed to 160, 400 or 1000 mg/m³ of DBE exhibited degeneration of olfactory epithelium. Rats exposed to 400 or 1000 mg/m³ had decreased liver/body ratios and slightly depressed body weights were observed in rats exposed to 1000 mg/m³. In the second 90-day inhalation study rats were exposed to 20, 76, 390 mg/m³ of DBE. Degeneration of olfactory epithelium was observed in rats exposed to 76 or 390 mg/m³ of DBE. In rabbits, a single 4-hr exposure to 60 ppm caused transient corneal opacity and transient increases in the distance from the cornea to the anterior surface of the lens of the eye. The administration of 10-100 μ L caused corneal opacity, transient increases in corneal thickness, and transient corneal anesthesia. A single application of approximately 60 mg/kg to th