

1. Product and Company Identification

www.rxmarine.com

Product Name Stone Professional High Gloss Finishing Sealer
Product Type RXSOL-41-8900-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax +91 22 2781 1318+ :::AOH :0091 9322594669
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Components

Material	CAS Number	%
Water	7-18-5	60-90
Styrene-Acrylic Copolymer	10-35	
Aromatic Glycol Esters		1-3
Dipropylene Glycol n-B732utyl Ether	29911-28-2	1-3
Polymeric Hydrocarbon	1-3	

3. Hazards Identification

www.rxmarine.com

Potential Health Effects

Eye Contact: May cause eye irritation. Skin Contact: May cause mild skin irritation.

Inhalation: Prolonged exposure is not expected to cause adverse effects.

Ingestion: Low toxicity if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

4. First Aid Measures

www.rxmarine.com

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

5. Fire-fighting Measures

www.rxmarine.com

Flammable Properties

Not a fire or explosion hazard.

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

6. Accidental Release Measures

www.rxmarine.com

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL)

sections before proceeding with clean-up. Use appropriate

PERSONAL PROTECTIVE EQUIPMENT

During clean-up. Initial Containment

Dike spill.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material.

7. Handling and Storage

www.rxmarine.com

Handling (Personnel)

Avoid inhalation.

Avoid contact with eyes, skin or clothing.

Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Avoid freezing or extended storage in high temperature.

8. Exposure controls and personal protection

www.rxmarine.com

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

Dipropylene Glycol n-Butyl Ether

AEL * (DuPont) : 50 ppm, 8 & 12 Hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

9. Physical and chemical properties

www.rxmarine.com

Odor :	(slight).
Color :	White.
Form :	Liquid Dispersion.
Density :	8.5 lb/gal
Viscosity :	