

1. Product and Company Identification

www.rxmarine.com

Product Name Stone Impregnator Professional Pro
Product Type **RXSOL-41-8905-025**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax +91 22 2781 1318 :::AOH :0091 9322594669
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Components

Material	CAS Number	%
Fluorinated Acrylic Copolymer		
Butyl Acetate	123-86-4	
Aliphatic Hydrocarbons	64742-48-9	
Wood Fragrance		

3. Hazards Identification

www.rxmarine.com

Potential Health Effects

Inhalation may cause respiratory irritation with headache, dizziness, nausea, or unconsciousness.

Skin contact may cause mild irritation.

Eye contact may cause mild irritation.

Ingestion may irritate stomach and intestines. May be aspirated into lungs if swallowed, resulting in pulmonary edema and chemical pneumonitis. Harmful or fatal if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

4. First Aid Measures

www.rxmarine.com

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. **DO NOT GIVE ANYTHING TO DRINK.** Call a physician immediately. Never give anything by mouth to an unconscious person.

5. Fire-fighting Measures

www.rxmarine.com

Flammable Properties

Flash Point : 108 F (42 C)

Method : Closed Cup.

Combustible liquid.

Extinguishing Media

Water, Foam, Dry Chemical, CO₂.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

6. Accidental Release Measures

www.rxmarine.com

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate **PERSONAL PROTECTIVE EQUIPMENT during clean-up.**

Wear self-contained breathing apparatus (SCBA) and full protective gear.

Initial Containment

Dike spill.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material. Shovel or sweep up.

7. Handling and Storage

www.rxmarine.com

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

Butyl Acetate

PEL (OSHA) : 150 ppm, 710 mg/m³, 8 Hr. TWA

TLV (ACGIH) : 150 ppm, 8 Hr. TWA

AEL * (DuPont) : None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

Exposure Guideline Comments

Aliphatic Hydrocarbon

TLV* (ACGIH) : 200 ppm

*Provided by Chevron Phillips

9. Physical and chemical properties

www.rxmarine.com

Evaporation Rate :	300 F (>149 C)
Odor :	Hydrocarbon (mild).
Form :	Liquid.
Color :	Colorless.
Specific Gravity :	0.75 25 C (77 F)

10. Stability and reactivity

www.rxmarine.com

Chemical Stability

Stable.

Incompatibility with Other Materials Incompatible with oxygen, strong oxidizing agents.

Decomposition

Thermal decomposition may produce carbon monoxide, carbon dioxide and hydrogen fluoride. Polymerization Polymerization will not occur.

11. Toxicological information

www.rxmarine.com

12. Ecological information

www.rxmarine.com

13. Disposal considerations

www.rxmarine.com

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transport information

www.rxmarine.com

Shipping Information

DOT: Not Regulated by DOT in packages with a capacity of less than 119 gallons.

IMDG:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.

Hazard Class : 3

UN Number : 3295

Packing Group : III

Label : Flammable Liquid

For 2 Oz., 1 Pint, 1 Quart, and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.

Hazard Class : 3

UN Number : 3295

Packing Group : III

Label : Flammable Liquid

Special Instructions : Limited Quantity

IATA:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.

Hazard Class : 3

UN Number : 3295

Packing Group : III

Label : Flammable Liquid

For 1 Quart and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.

Hazard Class : 3

UN Number : 3295

Packing Group : III

Label : Flammable Liquid

Special Instructions : Limited Quantity

For 2 Oz. and 1 Pint:

Proper Shipping Name : Consumer Commodity

Hazard Class : 9

UN Number :