

1. Product and Company Identification

www.rxmarine.com

Product Name
Part Number

BenzalKonium Chloride BKC
RXSOL-15-1599-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai, Chennai, Kakinada, Vizag, Kolkata, UAE, and Oman

Phone +91 22 2781 5540 / 41 / 42
Fax +91 22 2781 1318 ::::AOH :0091 9821214367
Email 123@rxmarine.com
Website www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	Cas Number
N-Alkyldimethylbenzyl ammonium chloride	8001-54-5
Water	7732-18-5
Proprietary	

3. Hazards Identification

www.rxmarine.com

Signal Word
Hazard Statements

Precautionary statements - prevention

Precautionary statements - response

Warning

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H400 Very toxic to aquatic life.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors thoroughly after handling
Do not eat, drink or smoke when using this product
Do not breathe dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection
Use only outdoors or in a well-ventilated area

Immediately call a POISON CENTER or doctor/physician if you feel unwell.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

Rinse mouth
Do NOT induce vomiting

Storage

Store locked up
Store in a well-ventilated place. Keep container

4. First Aid Measures

www.rxmarine.com

Skin Contact

Wash off immediately with plenty of water for 15 minutes. Remove clothing and gloves, including the inside, before re-entire.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids. If irritation persists, medical attention is required. Keep eye wide open while rinsing.

Inhalation:

Do not use mouth-to-mouth method if victim ingested or inhaled. Provide respiratory assistance with the aid of a pocket mask equipped with a one-way valve. Remove from exposure, lie down. Call a physician immediately for respiratory assistance.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to someone who is unconscious or who is choking. Call a physician immediately.

Most important symptoms/effects

Causes burns by all exposure routes. Ingestion causes severe irritation and danger of perforation.

Notes to Physician

Treat symptomatically

5. Fire-fighting Measures

www.rxmarine.com

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Do not use water spray to fire with water spray.

Unsuitable extinguishing media

No Information Available

Sensitivity to Mechanical Impact

No information available

Sensitivity to Static Discharge

No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. Irritation to eyes, skin and mucous membranes. Do not allow contact with skin or clothing.

Hazardous Combustion Products

Thermal decomposition can lead to release of irritating gases and vapors. Precautions for Firefighters As in any fire, wear self-contained breathing apparatus (SCBA) (MSHA/NIOSH (approved or equivalent) and full protective clothing. Avoid release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

Use personal protective equipment as required. Avoid breathing vapors. Use full protective clothing and self-contained breathing apparatus (SCBA).

Further Information

Do not flush into surface water or sanitary sewer system. Prevent product from entering drainage system. Spillages cannot be contained.

6. Accidental Release Measures

www.rxmarine.com

Spillage

Absorb with an inert material and put the spillage in a container for disposal. Flammable liquid. Keep away from heat. Keep away from open flames. Absorb with DRY earth, sand or other non-combustible material. Prevent entry into sewers, basements or confined spaces. If product is not present at a concentration level above TLV, no further action is required. Notify authorities.

Personal Protection

Use personal protective equipment. Ensure adequate ventilation.

Environmental Precaution

Methods and materials for containment and cleaning

Take precautionary measures against static discharges. Should not be released into the environment. See Section 6. Avoid release to the environment. Collect spillage. Do not use in confined spaces. Soak up with inert absorbent material. Keep in suitable containers away from sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

www.rxmarine.com

Handling

Storage

Hygiene measures

Wear personal protective equipment. Do not get in eyes, on skin or clothes. Use only in a well-ventilated area or chemical fume hood. Do not breathe vapors or spray mist. Keep away from flames, hot surfaces and sources of ignition. Use only in a well-ventilated area. Avoid vapors by static electricity discharge, all metal parts of equipment should be grounded. Take precautionary measures against static discharges. Keep containers tightly closed in a dry, cool and well-ventilated area away from sources of ignition. Flammables area. Corrosives area. Immediately change contaminated clothing. Apply preventive measures after working with substance.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Control

Personal Protection

Hygiene Measures

Exposure Limits

Provide exhaust ventilation or other engineering controls to keep vapors below their respective threshold limit value. Ensure that workers are proximal to the work-station location.

Eye/face Protection : Wear appropriate protective equipment as described by OSHA's eye and face protection regulation and European Standard EN166.

Skin and body protection : Wear appropriate protective clothing for exposure. Long sleeved clothing.Flame retardant antistatic clothing.

Respiratory Protection : Follow the OSHA respirator regulations in the European Standard EN 149. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safe practices. TWA: 100 (ppm) [Canada] TWA: 435 (mg/m3) [Canada] TWA: 100 (ppm) ACGIH (TLV) [United States] TWA: 100 STEL: 150 (ppm) from ACGIH (TLV) [United States] Do not exceed acceptable exposure limits.



Gloves Suit

9. Physical and chemical properties

www.rxmarine.com

Form	Liquid
Colour	Colourless
Odour	sweet, Characteristic
Odor Threshold	No Information Available
pH	Not Applicable
Melting Point	-25 °C / -13 °F
Boiling Point	143 - 145 °C / 289.4 - 293 °F
Flash Point	31 °C / 87.8 °F
Evaporation Rate	0.7
Flammability (solid, gas)	Not Applicable
Explosive limits	Upper 6.7 % Lower 0.9 %
Vapour pressure	No information available
Vapour Density	3.7
Secific Gravity	0.878
Decomposition Temperature	No information available
Partition coefficient	No data available
Autoignition Temperature	465 °C / 869 °F
Solubility in Water	Not Soluble
Viscosity	No information available
Molecular Formula	C8 H10
Molecular Weight	106.17

10. Stability and reactivity

www.rxmarine.com

Recativity Hazard	None known, based on information available
Stability	Product is stable.
Possibility of hazardous reactions	No known hazardous reactions.
Conditions to avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible materials	Strong oxidizing agents, Strong acids, Strong reducing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂),
Hazardous Polymerization	Hazardous polymerization does not occur. Hazardous Reactions None under normal processing

11. Toxicological information

www.rxmarine.com

Acute oral toxicity	Symptoms: Gastrointestinal disturbance, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration
Acute dermal toxic	Acute toxicity estimate : 1,134 mg/kg
Skin corrosion	Drying-out effect resulting in rough and chapped skin. Mixture causes skin irritation.
Toxic Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. Can be absorbed through skin. Eyes: Causes eye irritation. Vapor causes respiratory tract and mucous membrane irritation.
Special Remarks on Chronic Effects on Humans	Detected in maternal milk in human. Passes through the placental barrier in animal. Embryotoxic and/or foetotoxic. May cause adverse reproductive effects (male and female fertility (spontaneous abortion and fetotoxicity) and birth defects) and data.
Further information After absorption:	Headache, somnolence, Dizziness, euphoria, agitation, spasms, narcosis Effect potentiated by: ethanol Damage to: nervous system, Liver

12. Ecological information

www.rxmarine.com

Toxicity to Fish	No information available.
COD and BOD 5	Not Available
Products of Biodegradation:	No information available.
Mobility in soil	No information available.
Results of PBT and vPvB assessment	Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, a PBT/vPvB assessment was not conducted.
Other adverse effects	Additional ecological information Discharge into the environment must be avoided.

13. Disposal considerations

www.rxmarine.com

Waste treatment Method	Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original packaging with other waste. Handle uncleaned containers like the product itself
------------------------	---

14. Transport information

www.rxmarine.com

DOT

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

TDG

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

IATA

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

IMDG/IMO

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

15. Regulatory information

www.rxmarine.com

Federal and State Regulation

Connecticut hazardous material survey.: Xylenes Illinois acutely hazardous substances: Xylenes Rhode Island acutely hazardous substances: Xylenes Pennsylvania RTK: Xylenes Minnesota: Xylenes Michigan critical material: Xylenes Massachusetts RTK: Xylenes New Jersey: Xylenes New Jersey spill list: Xylenes Louisiana: Xylenes Director's List of Hazardous Substances: Xylenes 302/304/311/312 hazardous chemicals: Xylenes SARA 302/304/311/312 hazardous chemicals: Xylenes SARA 302/304/311/312 hazardous chemicals: Xylenes SARA 302/304/311/312 hazardous chemicals: Xylenes SARA 302/304/311/312 hazardous chemicals: Xylenes reporting: Xylenes CERCLA: Hazardous substances.: Xylenes

Other Regulation

OSHA: Hazardous by definition of Hazard Communication EINECS: This product is on the European Inventory of Existing Commercial Substances

WHMIS (Canada)

CLASS B-2: Flammable liquid with a flash point below 23°C (73°F) and above 23°C (73°F) and a boiling point at or above 35°C (95°F) Material causing other toxic effects (VERY TOXIC).

HMIS

Health Hazard	: 3
Fire Hazard	: 3
Reactivity	: 0
Personal Protection	: H

Fire :

Health Hazard	: 3
Fire Hazard	: 3
Reactivity	: 0
Specific Hazard	: ..

16. Other information

www.rxmarine.com

Other Information

The information above is believed to be accurate and available to us. However, we make no warranty of accuracy, implied, with respect to such information, and we should make their own investigations to determine its accuracy for particular purposes. In no event shall we be liable for any damages, for lost profits or any special, indirect, incidental, or consequential damages arising, even if **Rx Marine International** has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY :The information in this MSDS is believed to be reliable. However, the information is provided as is, and we do not assume responsibility for its correctness. The conditions or methods of use are beyond our control and may be beyond our knowledge. We do not assume responsibility and expressly disclaim liability for any damages in any way connected with the handling, storage, use or misuse of this product, and is to be used only for this product. If the product is used for any other purpose, the MSDS information may not be applicable.