

## 1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-26-3107-055

Product Type Activated Carbon

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing, BSEL, TECH PARK.  
VASHI, NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Vizag, Fujairah, Muscat

Phone +91 22 65113333 / 5555 / 9999 / 27611360

Fax +91 22 2781 1318 ::::AOH :0091 9821214367

Email [mail@rxmarine.com](mailto:mail@rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

### INGREDIENTS.

Chemical Name (CAS)	%	PEL(OSHA)	TLV(ACGIH)	Other
Carbon (7440-44-0)	100	N/A	N/A	N/A

\*ACGIH (TWA) for respirable dust is 2.5 mg/m<sup>3</sup>

There are no established PEL, TWA or TLV values for this material. Caution should be taken for respirable dust. The product has no known carcinogenic properties.

## 3. Hazards Identification

www.rxmarine.com

### HEALTH HAZARD DATA:

Route (s) of Entry:

Ingestion: Carbon is non-toxic through ingestion

Inhalation: The physical nature of carbon may irritate the respiratory system

Skin: Carbon is non-toxic through skin absorption.

Eye Irritation: The physical nature of carbon may cause, eye irritation.

## 4. First Aid Measures

www.rxmarine.com

### EMERGENCY & EIRST AID PROCEDURES:

In case of inhalation remove to fresh air. Administer first aid as appropriate. Seek medical attention.

In ease off ingestion do not induce vomiting. Dilute by giving water or milk. Seek medical attention.

Skin Contact: Wash thoroughly with water. If irritation persists seek medical attention.

In case of eye contact flush with lukewarm water for at least 15 minutes. Seek medical attention.

### OTHER:

The effects of chronic and sub-chronic exposure have not been determined. Safe handling on a long-term basis should emphasize protection against respective or long-term exposure to carbon dust inhalation and avoidance of contact to any liquids that may Leach off the impregnated carbon.

## 5. Fire-fighting Measures

www.rxmarine.com

### FIRE FIGHTING MEASURES

Flashpoint: Not Applicable.

Non-flammable: 16CFR1500.44.

Not Self Heating: UN Manual of Tests and Criteria, Test N.3.

Flammability Limits in Air: LFL and UFL Not Applicable.

**GENERAL HAZARD:**

Activated carbon is difficult to ignite and tends to burn slowly (smoulder) without producing smoke or flame. Toxic gases will form upon combustion.

**FIRE FIGHTING INSTRUCTIONS:**

If possible to do safely, move smouldering activated carbon to a non-hazardous area, preferably out of doors. Extinguish fire using water fog, fine water spray, carbon dioxide or foam. Avoid stirring up dust clouds.

**FIRE FIGHTING EQUIPMENT:**

Firefighting personnel should wear full protective equipment, including self-contained breathing apparatus (SCBA) for all inside fires and large outdoor fires.

**HAZARDOUS COMBUSTION PRODUCTS:**

Combustion products may include smoke and oxides of carbon (for example, carbon monoxide). Materials allowed to smolder for long periods in enclosed spaces may produce amounts of carbon monoxide which reach the lower explosive limit (carbon monoxide LEL = 12.5% in air). Under certain conditions, any airborne dust may be an explosion hazard. Used activated carbon may produce additional combustion products.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Fire Explosion Data

Flash Point: N/A

Extinguishing media: Alcohol foam, CO<sub>2</sub>, dry chemical, water.

Special Firefighting procedures: Exercise caution when responding to any chemical fire. Respiratory Protection is essential

Unusual fire & explosion hazards: Contact of activated carbon with strong oxidizers may cause rapid combustion.

Contact of Phosphoric acid with certain metals may liberate hydrogen which is flammable and readily forms explosive mixtures in air.

Decomposition Products: CO may be formed in the fire.

Thermal Decomposition: Sulfur Oxides (SO<sub>x</sub>)

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

**STORAGE AND HANDLING INFORMATION:**

Storage Temperature: Ambient

Storage Pressure: Atmospheric

Handling: Follow good handling and housekeeping practices to minimize spills, generation of airborne dust, and accumulation of dust on exposed surfaces.

Use with adequate exhaust ventilation to draw dust away from workers' breathing zones.

Prevent or minimize exposures to dust by using appropriate personal protective equipment.

Wash exposed skin areas thoroughly with soap and water after handling.

Storage: Dry airtight storage recommended. Maintain good housekeeping. Store away from strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc.

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

**SPECIAL PROTECTION INFORMATION:**

Respiratory Protection: Use NIOSH/MSHA approved respiratory protection equipment appropriate to the material and/or its concentration where airborne exposure is likely. If exposures cannot be kept to a minimum with engineering controls, consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer.

Ventilation/Local Exhaust: Essential in confined areas.

Eye Protection: Safety glasses or goggles with side shields are recommended for any type of handling. Where eye contact or dusty conditions may be likely, dust tight goggles are recommended. Have eye flushing equipment available.

Engineering Controls: Use local exhaust ventilation to control emissions near the source. Ventilation systems should be sized and configured to prevent exceeding of recommended or regulated exposure limits. Skin Protection: Avoid contact with the skin. Wear appropriate dust resistant clothing. Wash contaminated

clothing and clean protective equipment before reuse. Wash skin thoroughly after handling. Protective Gloves Recommended

Hygienic Practices: Wash thoroughly after handling.

## Airborne Exposure Guidelines:

### Recommended Exposure Limits Activated Carbon

8-hr TWA

Total Dust 10 mg/m<sup>3</sup>\*

Respirable Fraction 3 mg/m<sup>3</sup>\*

\*OSHA and ACGIH have not established specific exposure limits for this material. The recommended exposure limits for these activated carbon products are based on the Threshold Limit Values adopted by ACGIH for Particulates (insoluble) Not Otherwise Classified. The OSHA PEL for Nuisance Dust is 15 mg/m<sup>3</sup> (5 mg/m<sup>3</sup> respirable fraction).

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

### PHYSICAL DATA:

Specific Gravity, (H <sub>2</sub> O = 1):	3.5
Solubility in water:	Insoluble
Apparent Density:	0.45 - 0.50 g/cc
Vapor Pressure:	N/A
Melting Point:	N/A
Boiling Point:	N/A
Freezing Point:	N/A
Appearance and Odor:	Black granular, powder or extruded pellet, no odor

## 10. Stability and reactivity

[www.rxmarine.com](http://www.rxmarine.com)

Incompatibility. Avoid strong oxidizers and liquid acids.

Stable: Yes

Conditions to avoid: None

Hazardous Decomposition Products: Oxides of Carbon

Hazardous Polymerization: Will not occur

## 11. Toxicological information

[www.rxmarine.com](http://www.rxmarine.com)

### ECOLOGICAL AND TOXICOLOGICAL INFORMATION

This material, in its original state, is not harmful to the environment. Used activated carbon may exhibit characteristics of the adsorbed material.

This material is non-toxic in its original state. Used activated carbon may exhibit characteristics of the adsorbed material.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

OSHA Hazard Communication: See "Particulates not otherwise regulated," in Table Z-1, Standard, 29CFR1910.1200:of 29CFR1910.1000, "Limits For Air Contaminates".

CERCLA/SUPERFUND, 40CFR117, 302: Notification of spills of this material is not required.

SARA/SUPERFUND: Amendments and Reauthorization Act of 1986 (Title III), Sections 302, and 313:.

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40CFR355):

This product is not listed as an extremely hazardous substance.

SECTION 313 - LIST OF TOXIC CHEMICALS: This product is not listed.

Toxic Substances Control Act, 40CFR710: Activated carbon is on the inventory list.

Resource Conservation and Recovery Act: This product, in its original state, does not meet the criteria of hazardous waste.

### STATE REGULATIONS:

California Occupational Safety and Health: ☐ Not listed.

Massachusetts Substance List: ☐ Not listed.

New Jersey Right-to-Know: ☐ Not listed.

### 13. Disposal considerations

www.rxmarine.com

#### HMIS INDEX:

HMIS Index details are as follows,

HEALTH: 0  
FLAMMABILITY: 1  
REACTIVITY: 1  
PPE: E

### 14. Transport information

www.rxmarine.com

DOT (Department of Transportation)

Proper Shipping (Article) Name: Steam Activated Carbon, Non-Regulated OR Carbon, Activated, Non-Regulated

Shipping Class: Class 70

Hazard Class: Not applicable.

UN/NA Number: Not applicable.

Packing Group: Not applicable.

Freight Classification: STCC Code - #2899643 / NMFC #040560

DOT Marking: N/A

DOT Placard: N/A

Precautions to be taken in Transportation: N/A

### 15. Regulatory information

www.rxmarine.com

Precautions to be taken

in handling and storage: Avoid excessive contact with moisture. Activated carbon can be safely stored in any normal storage area, but away from sources of direct heat.

Other precautions: Wet activated carbon depletes oxygen from the air creating a severe hazard to workers in enclosed or confined spaces, sampling and work procedures for low oxygen levels should be taken whenever workers entering carbon vessels, enclosed or confined spaces.

### 16. Other information

www.rxmarine.com

#### KEEP OUT OF REACH OF CHILDREN

Although the information and recommendations set forth in this sheet are believed to be correct as of the date hereof, RX MARINE International makes no representation as to the completeness or accuracy of such information and recommendations. RX MARINE International shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication or use of or reliance upon such information and recommendations. You are encouraged to advise anyone working with or exposed to such products of the information contained herein. No Warranty, either expressed or implied, of merchantability or fitness or of any other nature with respect to the product or to the information and recommendations herein made hereunder.

**DISCLAIMER OF LIABILITY** :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.