

1. Product and Company Identification

www.rxmarine.com

Product Name DERUSTING SOLUTION
Part Number RXSOL-35-3502-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 27815540 / 27815541
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	Cas Number	EC Number	Wight %
Phosphoric acid	7664 -38 -2		57 - 62%
Surfactant	Proprietary		10 - 20%
Corrosion Inhibitor	Proprietary		15 - 25%

3. Hazards Identification

www.rxmarine.com

SignalWord	Warning
Hazard Statements	May be corrosive to metals. Harmful if swallowed. Causes severe skin burns and eye damage. Causes severe damage to the respiratory tract.
Precautionary statements - prevention	Keep only in original container. Do not breath dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product.
Precautionary statements - response	Absorb spillage to prevent material damage. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

4. First Aid Measures

www.rxmarine.com

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.
-------------	--

Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
Ingestion:	Do not induce vomiting. Obtain medical attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
Notes to Physician	Treat symptomatically

5. Fire-fighting Measures

www.rxmarine.com

Flammability	Non-flammable.
Flash Point	Not applicable.
Suitable extinguishing media	No information available
Hazardous combustion products	Product itself does not burn, but may decompose upon heating to product carbon monoxide, carbon dioxide, oxides of potassium and nitrogen oxide.
Protective Equipment	A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.
Fire Fighting Measures	Move container from fire area if it can be done without risk. Keep storage containers cool with water spray. Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

6. Accidental Release Measures

www.rxmarine.com

Small Spillage	Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dust. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Environmental Precaution	Do not let product enter drains.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up the affected area. Avoid generation of dust

7. Handling and Storage

www.rxmarine.com

Handling	Keep away from sparks or flame. Do not breathe dust or vapours. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. The acid reacts with water and can splatter acid onto personnel. When diluting, cautiously mix product and water together while stirring.
Storage	Store in corrosive resistant container with a resistant inner liner. Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Control

Provide general ventilation needed to maintain the concentration of vapour or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Personal Protection

Eye/face Protection : Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection: Wear appropriate protective gloves and clothing to prevent skin exposure. Respiratory Protection: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator exposure limits are exceeded or if irritation or other symptoms are experienced.

Other Protection Measure

Handle in accordance with good industrial hygiene and safety practice.

Exposure Limit

Phosphoric Acid TWA: 1 STEL: 3 (mg/m³) from ACGIH (TLV) [United States] TWA: 1 STEL: 3 (mg/m³) from OSHA (PEL) [United States] TWA: 1 STEL: 3 (mg/m³) from NIOSH TWA: 1 STEL: 3 (mg/m³) [Mexico] Consult local authorities for acceptable exposure limits



Gloves Suit

9. Physical and chemical properties

www.rxmarine.com

Form

Liquid

Colour

Clear

Odour

Mild

Odor Threshold

No Information Available

pH