

## 1. Product and Company Identification

www.rxmarine.com

Product Name **RXSOL-19-1212**  
Product Type **METHYL ETHYL KETONE**

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Fujairah, Muscat, Kolkata, Chennai, Visakhapatnam

Phone +91 22 27815541 / 42  
Fax +91 22 2781 1318 :::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

- ☐ Chemical characterization:
- ☐ CAS No. Description  
78-93-3 butanone
- ☐ Identification number(s)
- ☐ EINECS Number: 201-159-0
- ☐ Index number: 606-002-00-3

## 3. Hazards Identification

www.rxmarine.com

- ☐ Hazard description:
- ☐ Information concerning particular hazards for human and environment:  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
R 11 Highly flammable.  
R 36 Irritating to eyes.  
R 66 Repeated exposure may cause skin dryness or cracking.  
R 67 Vapours may cause drowsiness and dizziness.

## 4. First Aid Measures

www.rxmarine.com

|                    |  |
|--------------------|--|
| After inhalation   | Supply fresh air; consult doctor in case of complaints.  |
| After skin contact | Generally the product does not irritate the skin.  |
| After eye contact  | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. |
| After swallowing   | If symptoms persist consult doctor.  |

## 5. Fire-fighting Measures

www.rxmarine.com

|  |  |
|--|--|
| Suitable extinguishing agents                      | CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. |
| For safety reasons unsuitable extinguishing agents | Water with full jet  |
| Protective equipment                               | No special measures required.  |

## 6. Accidental Release Measures

www.rxmarine.com

Person-related safety precautions  
Measures for environmental protection  
Measures for cleaning/collecting

Wear protective equipment. Keep unprotected persons away.  
Do not allow to enter sewers/ surface or ground water.  
Dilute with plenty of water. Ensure adequate ventilation.

## 7. Handling and Storage

www.rxmarine.com

Handling

Information for safe handling

No special requirement

Information about fire - and explosion protection

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Storage

Requirements to be met by storerooms and receptacles

Store in a cool location.

Information about storage in one common storage facility

Not required.

Further information about storage conditions

Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.

## 8. Exposure controls and personal protection

www.rxmarine.com

☐ Additional information about design of technical facilities: No further data; see item 7.

☐ Ingredients with limit values that require monitoring at the workplace: 78-93-3 butanone

PEL (USA) 590 mg/m<sup>3</sup>, 200 ppm

REL (USA) Short-term value: 885 mg/m<sup>3</sup>, 300 ppm Long-term value: 590 mg/m<sup>3</sup>, 200 ppm

TLV (USA) Short-term value: 885 mg/m<sup>3</sup>, 300 ppm Long-term value: 590 mg/m<sup>3</sup>, 200 ppm BEI

IOELV (EU) Short-term value: 900 mg/m<sup>3</sup>, 300 ppm Long-term value: 600 mg/m<sup>3</sup>, 200 ppm

WEL (Great Britain) Short-term value: 899 mg/m<sup>3</sup>, 300 ppm Long-term value: 600 mg/m<sup>3</sup>, 200 ppm Sk

Additional information

The lists valid during the making were used as basis.

Personal protective equipment:

General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection

Not required.

**Trade name**

**Methyl Ethyl Ketone**

Protection of hands

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of material on consideration of the penetration times, rates of diffusion and the degradation

☐ Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and variances of manufacturer to manufacturer.

☐ Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed

☐ Eye protection

## 9. Physical and chemical properties

www.rxmarine.com

General Information

Form

Fluid

Colour

Colourless

Odour

Pleasant

☐ Change in condition

Melting point/Melting range

-86.3°C

Boiling point/Boiling range

79-80.5°C

Flash point

-4°C

Ignition temperature

514°C

Danger of explosion

Product is not explosive. However, formation of explosive air/vapour mixtures are possible

|                                  |                              |
|----------------------------------|------------------------------|
| Explosion limits                 |                              |
| Lower                            | 1.8 Vol %                    |
| Upper                            | 11.5 Vol %                   |
| Vapour pressure at 20°C          | 105hPa                       |
| Density at 20°                   | 0.804-0.807g/cm <sup>3</sup> |
| Solubility in / Miscibility with |                              |
| Water at 20°C                    | 290g/l                       |
| Viscosity                        |                              |
| Dynamic at 15°                   | 0.423 mPas                   |

## 10. Stability and reactivity

[www.rxmarine.com](http://www.rxmarine.com)

- ☒ Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- ☒ Dangerous reactions No dangerous reactions known.
- ☒ Dangerous decomposition products: No dangerous decomposition products known.

## 11. Toxicological information

[www.rxmarine.com](http://www.rxmarine.com)

☒ Acute toxicity:-

LD/LC50 values relevant for classification

|        |      |                     |
|--------|------|---------------------|
| Oral   | LD50 | 3300 mg/kg (rat)    |
| Dermal | LD50 | 5000 mg/kg (rabbit) |

Primary irritant effect:

on the skin No irritant effect.

on the eye Irritating effect.

Sensitization No sensitizing effects known.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

General notes

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted quantities of it to reach ground water, water course or sewage system.

## 13. Disposal considerations

[www.rxmarine.com](http://www.rxmarine.com)

☒ Product:

☒ Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

☒ Uncleaned packaging:

☒ Recommendation: Disposal must be made according to official regulations.

## 14. Transport information

[www.rxmarine.com](http://www.rxmarine.com)

☒ Land transport ADR/RID (cross-border)

☒ ADR/RID class 3 Flammable liquids

☒ Danger code (Kemler) 33

☒ UN-Number 1193

☒ Packaging group II

☒ Hazard label 3

☒ Description of goods 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE)

☒ Maritime transport IMDG

☒ IMDG Class: 3

☒ UN Number 1193

☒ Label 3

|                                      |   |
|--------------------------------------|---|
| ☒ Packaging group                    | II  |
| ☒ EMS Number                         | F-E,S-D                                   |
| ☒ Marine pollutant                   | No  |
| ☒ Proper shipping name               | ETHYL METHYL KETONE (METHYL ETHYL KETONE) |
| ☒ Air transport ICAO-TI and IATA-DGR |   |
| ☒ ICAO/IATA Class                    | 3   |
| ☒ UN/ID Number                       | 1193                                      |
| ☒ Label                              | 3   |
| ☒ Packaging group                    | II  |
| ☒ Proper shipping name               | ETHYL METHYL KETONE (METHYL ETHYL KETONE) |

## 15. Regulatory information

[www.rxmarine.com](http://www.rxmarine.com)

Labelling according to EU guidelines    The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

|                |  |
|----------------|--|
| Risk phrases   | 11 Highly flammable.                                     |
|                | 36 Irritating to eyes.                                   |
|                | 66 Repeated exposure may cause skin dryness or cracking. |
|                | 67 Vapours may cause drowsiness and dizziness.           |
| Safety phrases | 2 Keep out of the reach of children.                     |
|                | 9 Keep container in a well-ventilated place.             |
|                | 16 Keep away from sources of ignition - No smoking.      |

## 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

This information is based on our present knowledge. However, this shall not constitute a guarantee for an specific product features and shall not establish a legally valid contractual relationship

**DISCLAIMER OF LIABILITY :**The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.