

1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-60-6605-207
Product Type PETROLEUM ETHER 40-600C LR
Revised date

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat Barka

Phone +91 22 27815541 / 42
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Substance / Preparation : Petroleum Ether 40-60 0C

CAS No :8032-32-4

Substance. Contains no other components or impurities which will influence the classification of the product.

3. Hazards Identification

www.rxmarine.com

3.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : F; R11

Xn; R65

R66

R67 N; R51/53

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Carcinogenicity - Category 1B - Danger (CLP : Carc. 1B) H350

Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3-

Warning (CLP : STOT SE 3) H336

Specific Target Organ Toxicity - Repeated exposure - Category 2 - Warning (CLP:

STOT RE 2) H373

Aspiration hazard - Category 1 - Danger (CLP : Asp. Tox. 1) H304

Skin irritation - Category 2 - Warning (CLP : Skin Corr. 2) H315

Germ cell mutagenicity - Category 1B - Danger (CLP : Muta. 1B) H340

Physical hazards : Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

Environmental hazards : Hazardous to the aquatic environment - Chronic hazard-

Category 2 (CLP : Aquatic Chronic 2) H411

3.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s) : F : Highly flammable N :

Dangerous for the environment

Xn : Harmful

R Phrase(s) : R11 : Highly flammable.

R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 : Harmful : may cause lung damage if swallowed.

R66 : Repeated exposure may cause skin dryness or cracking.

R67 : Vapours may cause drowsiness and dizziness.

S Phrase(s) : S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S61 : Avoid release to the environment. Refer to special instructions/Safety data sheets.

S62 : If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms

Signal words : Danger

Hazard statements : H225 : Highly flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways

H350 : May cause cancer.

H340 : May cause genetic defects.

H315 : Causes skin irritation.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated exposure.

H411 : Toxic to aquatic life with long lasting effects.

Precautionary statements

☒ General : P201: Obtain special instructions before use

☒ Prevention : P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, , equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. ☒ No smoking.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.

P260: Do not breathe dust, fume, gas, mist, vapours, spray.

P273: Avoid release to the environment.

P233: Keep container tightly closed.

P264: Wash thoroughly after handling.

☒ Response : P301+P310: IF SWALLOWED : Immediately call a POISON CENTER or doctor.

P302+P352: IF ON SKIN : Wash with plenty of soap and water.

P308+P313: If exposed or concerned : get medical advice.

P332+P313: If skin irritation occurs : Get medical advice.

P391: Collect spillage.

P304+P340: IF INHALED : Remove to fresh air and keep at rest in a position comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse

P314: Get medical advice if you feel unwell.

P370+P378: In case of fire: Use for extinction.

☒ Storage : P403+P233: Store in well-ventilated place. Keep container tightly closed.

P403+P235: Store in well-ventilated place. Keep cool. P405: Store locked up.

☒ Disposal considerations : P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special labelling : Restricted to professional users. (Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008)

3.3. Other hazards

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

4. First Aid Measures

www.rxmarine.com

4.1. Description of first aid measures

Inhalation : Call a POISON CENTER or doctor if you feel unwell. Remove to fresh air and keep at rest in a position comfortable for breathing.

Skin contact : Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Specific treatment (see on this label). Get medical advice if skin irritation occurs

Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain blinking or redness persist.

Ingestion : Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : May cause cancer. May cause genetic defects.

Causes damage to organ.

May be fatal if swallowed and enters airways.

Causes skin irritation. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting Measures

www.rxmarine.com

5.1. Extinguishing media Suitable

extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Flammable class : Highly flammable liquid and vapour.

Hazardous combustion products : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment

6. Accidental Release Measures

www.rxmarine.com

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.

Ventilate area. Avoid breathing dust, fume, gas, mist, vapours, spray.

Technical measures : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and Storage

www.rxmarine.com

7.1. Precautions for safe handling

Handling : Handle empty containers with care because residual vapours are flammable.

Wash thoroughly after handling. Obtain special instructions before use. Eliminate all ignition sources if safe to do so. Use only outdoors or in a well-ventilated area.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be

followed. Use explosion-proof electrical, ventilating, lighting, , equipment.

Special precautions : No naked lights. No smoking. Avoid breathing dust, fume, gas mist, vapours, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed.

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight.

Heat sources.

7.3. Specific end use(s)

Specific end use(s) : None

8. Exposure controls and personal protection

www.rxmarine.com

8.1. Exposure controls

Personal protection : Avoid all unnecessary exposure.

☒ Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

☒ Hand protection : Wear protective gloves.

☒ Skin protection : Wear suitable protective clothing.

☒ Eye protection : Chemical goggles or safety glasses.

☒ Others : When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available

9. Physical and chemical properties

www.rxmarine.com

9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Liquid.

Odour : Gasoline or kerosene

Odour threshold : No data available.

pH value : No data available

. Melting point [°C] :

Decomposition point [°C] : N/A

Critical temperature [°C] : N/A

Auto-ignition temperature [°C] : 2880C

Flammability (solid, gas) : Flammable.

Highly flammable liquid and vapour.

Flash point [°C] : -40°C

Boiling point [°C] : 40 - 60 °C

Initial boiling point [°C] : 40 °C

Final boiling point [°C] : 60 °C

Evaporation rate : 10

Vapour pressure [20°C] : 40 mm Hg @ 20C

Vapour pressure mm/Hg : 40 mm Hg @ 20C

Vapour density : 2,5

Density [g/cm³] : 0.60 - 0.75

Relative density, gas (air=1) : N/A

Relative density, liquid (water=1) : N/A

Solubility in water [% weight] : Insoluble.

Solubility in water : N/A

Log Pow octanol / water at 20°C : No data available.

Solubility : N/A

Viscosity at 40°C [mm²/s] : N/A

9.2. Other information

Explosive properties : N/A

Explosion limits - upper [%] : 5,90%

Explosion limits - lower [%] : 1,10%

Oxidising properties : No data available

10. Stability and reactivity

10.1. Reactivity

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products : Fumes. Carbon monoxide.

Carbon dioxide. May release flammable gases.

11. Toxicological information

www.rxmarine.com

11.1. Information on toxicological effects

Acute toxicity

☒ Inhalation : May be fatal if swallowed and enters airways.

☒ Dermal : Based on available data, the classification criteria are not met.

☒ Ingestion : May be fatal if swallowed and enters airways.

Corrosion : Based on available data, the classification criteria are not met.

Irritation : Causes skin irritation.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

Toxic for reproduction : Based on available data, the classification criteria are not met.

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

12. Ecological information

www.rxmarine.com

12.1. Toxicity

Toxicity information : Toxic to aquatic life with long lasting effects.

12.2. Persistence - degradability

Persistence - degradability : May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

www.rxmarine.com

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special precautions : Handle empty containers with care because residual vapours are flammable. Hazardous waste due to toxicity.

14. Transport information

www.rxmarine.com

14.1. Land transport (ADR-RID)

Proper shipping name : PETROLEUM DISTILLATES, N.O.S. or PETROLEUM

PRODUCTS, N.O.S. (vapour pressure at 50 °C more than 110 kPa)

UN N° : 1268

H.I. nr : 33

ADR - Class : 3

Labelling - Transport : 3 : Flammable liquid.

ADR - Classification code : F1

ADR - Group : II

ADR - Packing instructions : P001

ADR - Limited Quantity : 1 L

ADR - Tunnel code : D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : PETROLEUM DISTILLATES, N.O.S. or PETROLEUM

PRODUCTS, N.O.S. (vapour pressure at 50 °C more than 110 kPa)

UN N° : 1268

IMO-IMDG - Class or division : 3 : Flammable liquid.

IMO-IMDG - Packing group : II

IMO-IMDG - Packing instructions : P001

IMO-IMDG - Limited quantities : 1 L

IMO-IMDG - Marine pollution : Yes

EMS-Nr : F-E S-E

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : PETROLEUM DISTILLATES, N.O.S. or PETROLEUM

PRODUCTS, N.O.S. (vapour pressure at 50 °C more than 110 kPa)

UN N° : 1268

IATA - Class or division : 3 : Flammable liquid.

IATA - Packing group : II

IATA - Passenger and Cargo Aircraft : ALLOWED

- Passenger and Cargo - Packing : 353

instruction - Passenger and Cargo - Maximum : 5 L

Quantity/Packing

IATA - Cargo only : ALLOWED

- Cargo only - Packing instruction : 364

- Cargo only - Maximum Quantity/ : 60 L

Packing IATA - Limited Quantities : 1 L

ERG-Nr : 3H

15. Regulatory information

www.rxmarine.com

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental : Ensure all national/local regulations are observed.

regulations/legislation specific for the substance or mixture

REACH Restrictions - Annex XVII : With the exception of those listed below:

The components of this product are not subject to restrictions.

Annex XVII

REACH Authorisation - Annex XIV : The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment : It has not been carried out.

16. Other information

www.rxmarine.com

Abbreviations and acronyms : PBT: persistent, bioaccumulative and toxic.

vPvB: very persistent and very bioaccumulative

Sources of key data used : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Further information : None

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.