

## 1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-18-2105-210  
Product Type Low Aromatic Solvent

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

**Stock Points: Mumbai, Kandla, Kolkata, Vishakhapatnam, Chennai, Fujairah, Muscat Oman, Kenya Africa, Canada**

Phone +91 22 27815541 / 42  
Fax +91 22 2781 1318 :::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmarine.com](http://www.rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	CAS #
Low aromatic petroleum solvent	8052-41-3

## 3. Hazards Identification

www.rxmarine.com

Swallowed	May cause symptoms of stomach pain, nausea and vomiting. Ingestion may cause unconsciousness. If vomiting occurs after ingestion, small amount of liquid may enter the lungs (aspiration) with the risk of chemical pneumonia induced.
Eye	Liquid may cause moderate to severe eye irritation, vapour is irritating
Skin	Contact with the product may cause defatting and contribute to dermatitis
Inhaled	Inhalation may cause headache, nausea and dizziness. Higher concentrations may cause unconsciousness and coma. Death may result from severe and continued exposure.
Chronic Effects	Inhalation and ingestion are the routes of entry into the body. The product may irritate the skin and prolonged or repeated contact may contribute to dermatitis.
Risk Phrase	R65 - Harmful: May cause lung damage if swallowed.

## 4. First Aid Measures

www.rxmarine.com

Skin	Remove contaminated clothing and wash thoroughly with soap and water. If soap is unavailable, use clean water. Apply a moisturising hand cream, if available. Seek medical attention if any soreness or inflammation of the skin persists. Launder affected clothing before re-use.
Inhalation	Remove to fresh air. Keep warm and at rest. If breathing is laboured, sit in an upright position (this assists respiration). Apply artificial respiration if breathing has stopped. Seek URGENT medical attention for all but the most minor exposures.
Safety Phrase	S2 - Keep out of reach of children S23 -Do not breathe vapour S24 -Avoid contact with skin S62 -If swallowed, do not induce vomiting: seek medical advice immediately, show container or label to medical staff.

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

FLAMMABLE

Solvent vapours can form explosive mixtures with air in poorly ventilated areas. Containers may explode if heated. Vapour is heavier than air and may collect in low ground, distant ignition is possible. Wear self contained breathing apparatus. Remove containers from the vicinity of the fire. Otherwise keep containers cool as far as possible by spraying with water, from a protected position.

Extinguishing Media

Foam, powder (bicarbonate or ammonium phosphate based) or carbon dioxide is not effective for fire fighting and direct contact with water should be avoided.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Care for environmental protection

Do not allow product to enter drains or waterways where ground or surface water may be affected.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

Storage / Transport: Class 3 Flammable Liquids should not be transported or stored with goods of:

Class 1 (Explosives)

Class 2.1 (Flammable gases, where both flammable liquid and flammable gases are in bulk)

Class 2.3 (Poisonous gases)

Class 4.2 (Spontaneously combustible substances)

Class 5.1 (Oxidising agents)

Class 6 (Poisonous (toxic) substances, where the flammable liquid is nitromethane)

Class 7 (Radioactive substances)

Store in a flammable liquids area, designated no smoking, away from all sources of ignition, out of direct sunlight in a cool well ventilated area below 25°C. Higher temperatures may cause pressure build up inside containers. Protect containers against physical damage. Ventilation along the floor is advised.

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

Personal Protection

Safety goggles, overalls and PVC gloves. A respirator with organic vapour filters is required unless the work area is well ventilated. In confined or poorly ventilated areas use air supplied breathing apparatus. NB: TAKE THE LIMITS OF RESPIRATOR CAPACITY INTO ACCOUNT. CHANGE FILTERS REGULARLY.

Flammability

FLAMMABLE. Solvent vapours can form flammable mixtures with air. The product may give off toxic fumes if heated or burned. The product may react with strong oxidising agents such as liquid or powdered chlorine. Not smoking.

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

Appearance / Odour

Water white liquid with a slight kerosene odour

Boiling Point

147°C - 196°C

Vapour Pressure

6mmHg

Specific Gravity

0.79

Flash Point

37°C

Explosive Limit (%)

L.E.L. 0.9% U.E.L. 7.0%

Solubility in Water