

1. Product and Company Identification

www.rxmarine.com

Product Name **RXSOL 70-7009-020**
Product Type **FUEL CARE 20 Ltr**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Fujairah, Muscat, Vizag, Nairobi

Phone +91 22 65113333 / 5555 / 9999 / 27611360
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

| Chemical Name | Concentration | CAS Number | EC Number | R Phrases* |
|---|---------------|------------|-----------|---------------|
| Kerosine-unspecified | 60-100 | 64742-94-5 | 265-198-5 | 65,66, 51, 53 |
| Naphtha(petroleum), hydro desulfurized heavy | 10-30 | 64742-82-1 | 265-185-4 | 65,66 |

Fatty Alcohol Polyethoxylated Polymer Exemption 1-30%

Manganese Oxide 655-19-9 10-20%

Tall oil hydroxyethyl imidazoline 61791-39-7 2631712 10 - 30 C 34

3. Hazards Identification

www.rxmarine.com



Harmful

| | |
|-------------------|---|
| Odour | Smells of hydrocarbon |
| Appearance | Liquid, pale yellow, insoluble in water |
| Contact with eyes | Causes redness and irritation |
| Contact with skin | Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis |
| Inhalation | In cases of severe exposure, dizziness, confusion, headache or stupor may develop |
| Ingestion | Harmful: may cause lung damage if swallowed (R65) Toxic to aquatic organisms, may cause long-term adverse effects on the environment (R51/53) |

4. First Aid Measures

www.rxmarine.com

| | |
|------------|--|
| Ingestion | Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention |
| Inhalation | Remove patient to fresh air Seek medical attention if ill effects occur |
| General | In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45) |

5. Fire-fighting Measures

www.rxmarine.com

- Auto-ignition point >200 deg C at 760 mm Hg
- Flash point >62 deg C (CC)
- Carbon oxides may be formed
- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide (S43)
- Do not use water jets
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
- Prevent run off water from entering drains if possible
- Wear Breathing Apparatus

6. Accidental Release Measures

www.rxmarine.com

| | |
|---------------------------|---|
| Personal Precautions | Wear protective clothing as per section 8 |
| Environmental Precautions | Do not allow to enter public sewers and watercourses Do not flush spilt material into any public water system |
| Immediate Actions | Contain spillage by any means possible |
| Clean Up Actions | Absorb spillage in inert material and shovel up Ventilate the area and wash spill site after material pick-up is complete |
| Special Precautions | Do not allow to enter public sewers and watercourses Wear protective clothing as per section 8 |

7. Handling and Storage

www.rxmarine.com

| | |
|----------|--|
| Handling | Avoid contact with skin and eyes (S24/25) Do not breathe vapours excessively Keep away from heat and sources of ignition |
| Storage | Keep only in the original container in a cool, well ventilated place (S3/9/49) Keep container tightly closed (S7) Keep away from flames, hot surfaces and sources of ignition. |

8. Exposure controls and personal protection

www.rxmarine.com

| | |
|--------------------------------|--|
| Exposure Limits | TLV (TWA) 120 mg/m ³ (Kerosine, unspecified) TLV (TWA) 275 mg/m ³ (Naphtha (petroleum) hydrodesulfurized) |
| Exposure controls | The undiluted product must not be used in a confined space without good ventilation No special ventilation is required if the product is used in a spray form. |
| Occupational exposure controls | No respiratory protection is required unless subject to contact with substance mist Where an air-purifying respirator is used, EN141 or EN405, type A |



Gloves Suit Goggles No_Smoking

9. Physical and chemical properties

www.rxmarine.com

| | |
|--------------------------|---|
| Odour | Smells of hydrocarbon |
| Appearance | Liquid, pale yellow, insoluble in water |
| pH | not applicable |
| Boiling point | 175 °C to 215 °C at 760 mm /Hg |
| Vapour pressure | not known |
| Vapour density (air = 1) | >1 |

| | |
|----------------------------|-------------------------|
| Melting point | not known |
| Insoluble in water | |
| Specific gravity (water=1) | 0.86 |
| Flash point | >62 deg C (CC) |
| Auto-ignition point | >200 deg C at 760 mm Hg |
| Lower explosive limit | 0.6 % (in air) |
| Upper explosive limit | 7 % (in air) |

10. Stability and reactivity

www.rxmarine.com

- This article is considered stable under normal conditions
- Keep away from naked flames, incandescent or hot surfaces
- See Section 5

11. Toxicological information

www.rxmarine.com

| | |
|---------------------------|---|
| Toxicological information | LD50 (oral) : >2000 mg/kg (Kerosine / naphtha). |
| Inhalation | Inhalation of solvent vapours may give rise to nausea, headaches and dizziness. |
| Contact with skin | Causes redness and irritation Prolonged skin contact will result in defatting of the skin, leading to irritation, a dermatitis. |
| Contact with eyes | Causes redness and irritation Ingestion The ingestion of significant quantities may cause damage to lungs Carcinogen of carcinogenic effects. |

12. Ecological information

www.rxmarine.com

| | |
|----------------------------------|---|
| Ecotoxicity | This product contains components which are classified in the EU as dangerous for the environment. Toxic to aqua cause long-term adverse effects in the aquatic environment (R51/53) LC50 96 hours fish 1-10 mg/l (Kerosine) L 10-100 mg/l (Naphtha) |
| Mobility | Insoluble in water |
| Persistence and Biodegradability | BOD 28 >60% |
| Bioaccumulation Potential | Hydrocarbon solvents have the potential to bioaccumulate. |
| Other Adverse Effects | No environmental problems are expected when the product is used / handled correctly. In its intended use, the p released into the environment. |

13. Disposal considerations

www.rxmarine.com

| | |
|-------------------------|--|
| Classification | EU Waste class: 07.01 This material and/or its container must be disposed of as hazardous waste |
| Disposal considerations | Do not discharge into drains or the environment, dispose to an authorised waste collection point Disposal should be i local, state or national legislation |

14. Transport information

www.rxmarine.com

| | | | |
|----------------------|----------------------|--|--------------------|
| Proper Shipping Name | | | |
| UN | Proper Shipping Name | Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes) | |
| | UN NO. | 3082 | |
| | Hazard Class | 9 | Packing Group III |
| Road/Rail (ADR/RID) | Proper Shipping Name | Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes) | |
| | ADR UN No. | 3082 | |
| | ADR Hazard Class | 9 | Termcard 90GM6-III |
| Sear (IMDG) | | | |

| | | | | |
|--|------------------------|--|----------------------|-----|
| Air(ICA0/IATA) | Proper Shipping Name | Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes) | | |
| | IMDG UN No. | 3082 | | |
| | IMDG Hazard Class | 9 | IMDG Pack Group | III |
| | IMDG EmS | F-A, S-B | IMDG subrisk | - |
| | IMDG Labels | 9+MarinePollutant | | |
| | IMDG Flashpoint | >62°C | | |
| DOT/CFR(USDepartment ofTransportation) | ProperShippingName | Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes) | | |
| | ICAO UnNo. | 3082 | | |
| | ICAO HazardClass. | 9 | ICAO PackingGroup. | III |
| | ICAO subrisk | - | ICAO Labels | 9 |
| | ICAO Flashpoint | >62°C | | |
| DOT/CFR(USDepartment ofTransportation) | DOTProperShippingName: | Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes) | | |
| | HazardousMaterial | (Alkyl (C3-C8) Benzenes) | | |
| | Hazard Class | 9 | IdentificationNumber | |
| | Product RQ (lbs) | Not Established | | |
| | DOTsubrisk: | - | | |
| | DOTLabels | 9+Marinepollutant | | |
| | DOTFlashpoint | | | |

15. Regulatory information

www.rxmarine.com

| | |
|----------------|---|
| Risk Phrases | Harmful: may cause lung damage if swallowed (R65) Repeated exposure may cause skin dryness or cracking (R66) Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R51/53) |
| Safety Phrases | Do not breathe spray/mists Avoid contact with skin Wear suitable protective clothing, eye/face protection and gloves Do not empty into the environment. Refer to special instructions/Safety data sheets. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. |

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:- R51: Toxic to aquatic organisms; R53: May cause long term adverse effects in the aquatic environment; R65: Harmful: may cause lung damage if swallowed; R66: Repeated exposure may cause skin dryness or cracking. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.