

1. Product and Company Identification

www.rxmarine.com

Part Number RXSOL-44-2065-025
Product Name Corrosion Inhibitor for Carbon Dioxide and H2S

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Muscat, Fujairah, Nairobi, Kolkata, Vizag, Chennai, Gandhidham, Canada

Phone +91 22 27815540 / 41 / 42
Fax +91 22 2781 1318 ::: AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

This product is classified as dangerous in accordance with the Preparations Directive 1999/45/EC.

Hazardous Substance	EINECS /	SYMBOL	R-PHRASES /	% (w/w)
	ELINCS NO		NOTAS	
Imidazoline Salts	Proprietary	Xi	R38, R41,R52/53	5 - 10
Quaternary Ammonium compound	Proprietary	C, N	R22, R34, R50	1 - 5
Proprietary Blend Non Hazardous Mixture				81-90

Refer to Section 16 for descriptions of relevant risk phrases and Notas.

3. Hazards Identification

www.rxmarine.com

HAZARD CLASSIFICATION :

Toxic by inhalation, in contact with skin and if swallowed. Irritating to eyes and skin

HUMAN HEALTH HAZARDS - ACUTE : INHALATION :

Toxic by inhalation. Repeated or prolonged exposure may irritate the respiratory tract.

SKIN CONTACT :

Contact with skin can cause moderate irritation

EYE CONTACT

Irritating, and will injure eye tissue if not removed promptly

INGESTION :

Not a likely route of exposure. Toxic if swallowed

PHYSICAL AND CHEMICAL HAZARDS

Combustible

4. First Aid Measures

www.rxmarine.com

INHALATION :

Remove to fresh air, treat symptomatically. If symptoms develop, seek medical advice

SKIN CONTACT

Immediately flush with plenty of water for at least 15 minutes. If symptoms develop, seek medical advice.

EYE CONTACT

Immediately flush eye with water for at least 15 minutes while holding eyelids open. If symptoms develop, seek medical advice.

INGESTION

Do not induce vomiting without medical advice. If conscious, washout mouth and give water to drink. If reflexive vomiting occurs, rinse mouth

NOTE TO PHYSICIAN

and repeat administration of water.

Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition

5. Fire-fighting Measures

www.rxmarine.com

FLASH POINT :

Not applicable

EXTINGUISHING MEDIA

Not expected to burn. Use extinguishing media appropriate for surrounding fire.

FIRE AND EXPLOSION HAZARD

Not flammable or combustible.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTING

In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit

6. Accidental Release Measures

www.rxmarine.com

PERSONAL PRECAUTIONS

Restrict access to area as appropriate until clean-up operations are complete. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection). Stop or reduce any leaks if it is safe to do so. Ventilate spill area if possible. Ensure clean-up is conducted by trained personnel only. Do not touch spilled material. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Notify appropriate government, occupational health and safety and environmental authorities.

METHODS FOR CLEANING UP

SMALL SPILLS: Soak up spill with absorbent material. Place residues in a suitable, covered, properly labeled container. Wash affected area.

LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or by diking. Reclaim into recovery or salvage drums or tank truck for proper disposal.

ENVIRONMENTAL PRECAUTIONS

Do not contaminate surface water

7. Handling and Storage

www.rxmarine.com

HANDLING

Do not get in eyes, on skin, on clothing. Do not take internally. Use with adequate ventilation. Do not breathe vapors/gases/dust. Keep the containers closed when not in use. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Ensure all containers are labeled

STORAGE CONDITIONS

Store in suitable labeled containers. Store the containers tightly closed. Amine and sulphite products should not be stored within close proximity or resulting vapors may form visible airborne particles. Avoid direct sunlight. At temperatures greater than 50°C may decompose exothermically with release of sulphur dioxide. 12 month shelf life under given storage conditions

SUITABLE CONSTRUCTION MATERIAL

Teflon, Perfluoroelastomer, PTFE, TFE, FEP (encapsulated), HDPE (high density polyethylene), Viton, Neoprene, Polypropylene, Stainless Steel 304, Stainless Steel 316L, Nitrile, EPDM

UNSUITABLE CONSTRUCTION MATERIAL

Brass, Aluminum, Mild steel, Carbon Steel C1018

SPECIFIC USE(S)

OXYGEN SCAVENGER

For specific dosages and customized applications please contact your representative

8. Exposure controls and personal protection

www.rxmarine.com

MONITORING MEASURES

A small volume of air is drawn through an absorbant or barrier to trap the substance(s) which can then be desorbed or removed and analyzed as referenced below

ENGINEERING MEASURES

The use of local exhaust ventilation is recommended to control emissions

near the source. Laboratory samples should be handled in a fumehood.
Provide mechanical ventilation of confined spaces

PERSONAL PROTECTION

GENERAL ADVICE

The use and choice of personal protection equipment is related to the hazard of the product, the workplace and the way the product is handled. In general, we recommend as a minimum precaution that safety glasses with side-shields and workclothes protecting arms, legs and body be used. In addition any person visiting an area where this product is handled should at least wear safety glasses with side-shields. The applicable European standard can be found in EN 166 .

RESPIRATORY PROTECTION

Where concentrations in air may exceed the limits given in this section, the use of a half face filter mask or air supplied breathing apparatus is recommended. A suitable filter material depends on the amount and type of chemicals being handled. Consider the use of filter type: E The applicable European standard can be found in EN 140, EN 137, EN 143 and EN 14387. In event of emergency or planned entry into unknown concentrations a positive pressure, full-facepiece SCBA should be used. If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection

HAND PROTECTION

When handling this product, the use of chemical gauntlets is recommended. The choice of work glove depends on work conditions and what chemicals are handled, but we have positive experience under light handling conditions using gloves made from PVC Gloves should be replaced immediately if signs of degradation are observed. Breakthrough time not determined as preparation, consult PPE manufacturers. The applicable European standard can be found in EN 374

SKIN PROTECTION

When handling this product, the use of overalls, a chemical resistant apron and rubber boots is recommended. The applicable European standard can be found in EN ISO 20345

EYE PROTECTION

Wear chemical splash goggles. The applicable European standard can be found in EN 166

HYGIENE RECOMMENDATIONS

Use good work and personal hygiene practices to avoid exposure. Keep an eye wash fountain available. Keep a safety shower available. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse. Always wash thoroughly after handling chemicals. When handling this product never eat, drink or smoke

9. Physical and chemical properties

www.rxmarine.com

PHYSICAL STATE	Liquid
APPEARANCE	Yellow Clear
ODOR	Pungent
FLASH POINT	Not applicable
SPECIFIC GRAVITY	1.035 (16 °C)
SOLUBILITY IN WATER	Complete
pH	6
VISCOSITY	Calculated 10cst
MELTING POINT	-20 °C
INITIAL BOILING POINT	100 °C Calculated
VAPOR PRESSURE	3.2 kPa (25 °C)
EVAPORATION RATE	1.5 (BuAc = 1)

Note: These physical properties are typical values for this product and are subject to change

10. Stability and reactivity

www.rxmarine.com

STABILITY	This material is unstable at elevated temperatures, which may cause exothermal decomposition
HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID	Hazardous polymerization will not occur At temperatures greater than 50°C may decompose exothermically with release of Sulphur dioxide gas
MATERIALS TO AVOID	SO ₂ may react with vapors from neutralizing amines and may produce a visible cloud of amine salt particles., Contact with strong acids (e.g. sulfuric, phosphoric, nitric, hydrochloric, chromic, sulfonic) may generate heat, splattering or boiling and toxic vapors
HAZARDOUS DECOMPOSITION PRODUCTS Under fire conditions	Amine

11. Toxicological information

www.rxmarine.com

No toxicity studies have been conducted on this product

SENSITIZATION
CARCINOGENICITY

Sulfites can cause an allergic reaction in sensitive individuals
None of the substances in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the American Conference of Governmental Industrial Hygienists (ACGIH).

For additional information on the hazard of the preparation, please consult section 2 and 12.

12. Ecological information

www.rxmarine.com

ECOTOXICOLOGICAL EFFECTS

MOBILITY