

1. Product and Company Identification

www.rxmarine.com

Product Name : ALKALINE HD coal remover **COAL REMOVER RX HOLD**
Product Type : **Cargo Hold Cleaner** RXSOL-22-3018-220

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai Ennore, Vizag Gangavaram, Kolkata Haldia, Fujairah, Muscat, Nairobi Kenya

Phone : +91 22 27815541 / 42
Fax : +91 22 2781 1318 ::AOH :0091 9821214367
Email : mail@rxmarine.com/

2. Composition / Information on ingredients

www.rxmarine.com

Chemica Name	CAS #	% BY WEIGHT
NaOCl	7681-52-9	40-50
Proprietary Blend of Surfactant and Corrosion Inhibitor	NA	60-40

3. Hazards Identification

www.rxmarine.com

Eye	Can cause permanent eye injury. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure the cornea and cause blindness.
Skin	Can cause permanent skin damage. Symptoms may include redness, burning, and swelling of skin, burns, and other skin damage. Additional symptoms of skin contact may include: skin blistering, hair loss, Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.
Swallowing	Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury.
Inhalation	It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract.
Target Organ Effects	This material (or a component) has been shown to lower activity of certain immune system cells in experimental animals. The significance of this effect with respect to human health is uncertain.
Developmental Information	There are no data available for assessing risk to the fetus from maternal exposure to this material.
Primary Route(s) of Entry	Inhalation, Skin contact, Eye contact.

4. First Aid Measures

www.rxmarine.com

Eyes	If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.
Skin	Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and discard contaminated shoes.
Swallowing	Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.
Inhalation	If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention, keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.
Note to Physicians	Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), immune system.

5. Fire-fighting Measures

www.rxmarine.com

Flash Point	Not applicable
Explosive Limit	Not applicable
Autoignition Temperature	No data
Hazardous Products of Combustion	NA
Fire and Explosion Hazards	No special fire hazards are known to be associated with this product.
Extinguishing Media	Use an extinguishing media appropriate for surrounding fire..
Fire Fighting Instructions	Water may be used to keep fire-exposed containers cool until fire is out. self-contained breathing apparatus with a full facepiece operated in the pressure demand mode with appropriate turn-out gear and chemical personal protective equipment. Refer to the personal protective equipment section of this MSDS.

6. Accidental Release Measures

www.rxmarine.com

Small Spill	Dilute with water and absorb onto a noncombustible absorbent material.
Large Spill	Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Collect and add slowly to large volume of water. Persons not wearing protective equipment should be excluded from area of spill until clean-up is completed. Stop spill at source. Dike to prevent spreading. Pump to salvage tank.

7. Handling and Storage

www.rxmarine.com

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Emergency eyewash fountains and safety showers should be available in the immediate vicinity of potential exposure

8. Exposure controls and personal protection

www.rxmarine.com

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious clothing and boots..

Respiratory Protections

If overexposure has been determined or documented, a NIOSH/MSHA jointly approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier.) Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of over exposure (from known, suspected or apparent adverse effects).

Exposure Guidelines

Component

9. Physical and chemical properties

www.rxmarine.com

Boiling Point

For component 212.0 F (100.0 C)

Vapor Pressure

For component) 17.500 mmHg

Specific Vapor Density

No data

Specific Gravity

>1 @ 68.00 F

Liquid Density

10.400 lbs/gal @ 68.00 F 1.250 kg/l @ 20.00 C

Percent Volatiles

87.5%

Evaporation Rate

SLOWER THAN ETHYL ETHER

Appearance

No data

State

LIQUID

Physical Form

HOMOGENEOUS SOLUTION

Color

CLEAR TO YELLOW LIQUID

Odor

CHLORINATED

pH

12.5-13.50

Solubility in Water

SOLUBLE

10. Stability and reactivity

www.rxmarine.com

Hazardous Polymerization

Product will not undergo hazardous polymerization.

- This article is considered stable under normal conditions
- Avoid overheating, Keep away from frost
- Incompatible with acid

11. Toxicological information

www.rxmarine.com

Toxicological information	No experimental data available.
Inhalation	Can cause damage to the respiratory system.
Contact with skin	Causes severe burns (R35).
Contact with eyes	Causes severe burns (R35).
Ingestion	The ingestion of significant quantities may cause burning sensation. The ingestion of significant quantities may cause damage to the digestive system.
Carcinogenicity	No evidence of carcinogenic effects.

12. Ecological information

www.rxmarine.com

Ecotoxicity	In general, this cleaning agent biodegradable to the environment, its main ingredients will either dissolve rapidly and completely or are readily/inherently biodegradable.
Mobility	Completely soluble in water
Persistence and Biodegradability	Its main ingredients will either dissolve rapidly and dissociate in water or are readily / inherently biodegradable.
Bioaccumulation Potential	Bioaccumulation of the components in this product is insignificant.
Other Adverse Effects	No effects in the environment. No environmental problems are expected when the product is used / handled correctly.

13. Disposal considerations

www.rxmarine.com

Classification	This material and/or its container must be disposed of as disposal waste. EU Waste class: 06 02 02
Disposal considerations	Disposal should be in accordance with local, state or national legislation

14. Transport information

www.rxmarine.com

DOT Information	49 CFR 172.101
DOT Description:	Mixture HYPOCHLORITE SOLUTIONS, 8, UN1791, III
Container/Mode:	55 GAL DRUM/TRUCK PACKAGE
NOS Component:	Not applicable
RQ (Reportable Quantity)	- 49 CFR 172.101
Product Quantity (lbs)	Component

15. Regulatory information

www.rxmarine.com

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: No Fire: No Pressure: No
Reactivity: No (Mixture / Liquid)

Australian Hazchem Code: None allocated.

Poison Schedule: S5

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

R35: Causes severe burns. R41: Risk of serious damage to eyes. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.