

1. Product and Company Identification

www.rxmarine.com

Product Name	Corrosion Inhibitor for Central Air Chiller
Part Number	RXSOL-44-9001-300
Chemical Family	Inorganic Bromide
Type of product and use	Inorganic solution used as desiccant medium in air conditioning and cooling

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat OMAN, Kenya, Canada

Phone	+91 22 27815540 / 41 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	123@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	Cas Number	EC Number	Wight %
Lithium Bromide	7550-35-8	231-439-8	55
Lithium Molybdate	13568-40-6	236-977-7	1-2
Proprietary Blend	-	-	40-50

3. Hazards Identification

www.rxmarine.com

Signal Word	Warning
Adverse human health effects	Risk of serious damage to eyes.

4. First Aid Measures

www.rxmarine.com

Eye Contact:	Holding the eyelids apart flush eyes promptly with copious amounts of water. Get medical attention immediately.
Skin Contact :	Remove contaminated clothing. Wash skin thoroughly with plenty of water for at least 15 minutes. Wash clothing before reuse. Get medical attention if irritation persists.
Inhalation:	In case of inhalation or breathing fumes released from the product, move to fresh air. Keep him quiet and warm. Apply artificial respiration if breathing has stopped. Get medical attention immediately.
Ingestion:	If swallowed, wash mouth thoroughly with plenty of water. Do not induce vomiting. Get medical attention immediately. NEVER GIVE AN UNCONSCIOUS PERSON ANYTHING BY MOUTH.

5. Fire-fighting Measures

www.rxmarine.com

Flash Point	None.
Auto-ignition	Not Available.

temperature

Flammable/Explosio
nlimits

Not Available

E extinguishing media
Fire fighting procedure

Material is not combustible. Use extinguishing media appropriate to surrounding fire conditions.

Cool containers with water spray. In closed stores, provide fire-fight self-contained breathing apparatus in positive pressure mode.

Usual fire and
explosion hazards

None known.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions

Wear respirator, chemical sa
and boots.

After spillage / leakage

Absorb on sand or vermiculite and place in closed co
site after material pick-up is complete. Avoid access

Disposal Considerations

Avoid access to streams, lakes or ponds.Observe all
when disposing of this material.

7. Handling and Storage

www.rxmarine.com

Handling
Storage

Avoid bodily contact. Keep containers tightly closed.
Store in a cool, well-ventilated area away from incom

8. Exposure controls and personal protection

www.rxmarine.com

Ventilation requirements
Personal protection equipment
Respiratory protection :
Gloves :
Eye Protection:
Others :
Industrial hygiene :

Provide adequate ventilation. Use local exhaust as necessa

Approved respirator.

Rubber gloves.

Chemical safety goggles.

Body covering clothes and boots.

Safety shower and eye bath should be provided.Do n
showering and changing clothes.

9. Physical and chemical properties

www.rxmarine.com

Appearance: Clear, colourless to yellow liquid, odourless.

Melting Point / range : 10oC (58%)

Boiling Point / range : 145 - 147oC (55%)

Vapour Pressure : 2.1 mm Hg at 20oC (55%)

Relative vapour density (air=1) : Not available.

Evaporation rate (either=1) : Not available.

Solubility in Water : 70 gr/100ml at 101oC

Solubility in other Solvent: Miscible with Methanol, Ethanol (absolute),n-Propanol.

Thermal decomposition : Not available.

10. Stability and reactivity

www.rxmarine.com

Stability Stable under normal conditions.
Materials to avoid : Strong acids.
Conditions to avoid : None known.
Hazardous decomposition-products : Hydrobromic Acid gas above 200oC
Hazardous Polymerization: Will not occur.

11. Toxicological information

www.rxmarine.com

Effect of overexposure
Ocular : Severe irritant.
Dermal : Mild irritant to intact skin.
Inhalation : May irritate the upper respiratory tract.
Ingestion : May cause vomiting, nausea, diarrhea and ataxia. Slurred speech, blurred vision, dizziness, sensory loss, convulsions and occur in cases of large intake.
Chronic toxicity : Repeated skin contact may cause dermatitis.Repeated oral intake of bromides may affect the central nervous system. Symptoms include mental dullness, slurred speech,weakened memory, apathy, anorexia, constipation, drowsiness and loss of sensitivity to touch and pain.
Carcinogenicity : Not known to be a carcinogen.
Mutagenicity : Not mutagenic by the Ames Test.

12. Ecological information

www.rxmarine.com

Aquatictoxicity : 48 Hour-EC50
Daphnia magna : 45 mg/l

13. Disposal considerations

www.rxmarine.com

Waste treatment Method Avoid access to streams, leaks or ponds. Observe all federal, state and local environmental regulations when disposing of

14. Transport information

www.rxmarine.com

UN No. : Not regulated.
IMO-IMDG CODE : Not regulated.
ICAO / IATA : Not regulated.
RID / ADR : Not regulated.
US DOT : Not regulated.

15. Regulatory information

www.rxmarine.com

Classification : Irritant symbol required and dangerous to the environment
R Phrase(s) : R 41 : Risk of serious damage to eyes.
R 52 : Harmful to aquatic organisms.
S Phrases : S 26 : In case of contact with eyes, rinse immediately
S 39 : Wear eye / face protection.
S 61 : Avoid release to the environment. Refer to product label for more details.

16. Other information

www.rxmarine.com

Revision Information:

None

Other Information

The information above is believed to be accurate and available to us. However, we make no warranty of accuracy, implied, with respect to such information, and we should make their own investigations to determine its accuracy for particular purposes. In no event shall we be liable for any damages, for lost profits or any special, indirect, incidental, or consequential damages arising, even if **RX Marine International** has been advised in writing.

DISCLAIMER OF LIABILITY :The information in this document is believed to be reliable. However, the information is provided without warranty regarding its correctness. The conditions or methods of use are beyond our control and may be beyond our knowledge. We do not assume responsibility and expressly disclaim liability for any damages in any way connected with the handling, storage, use or misuse of this product and is to be used only for this product. If the product is used for any other purpose, MSDS information may not be applicable.