

## 1. Product and Company Identification

www.rxmarine.com

Product Name Methanol  
Part Number RXSOL-19-2103-050

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400  
Fax +91 22 27612100 ::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmarine.com](http://www.rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Cas No	EC No	Whight	Formula
Methanol for spectroscopy Uvasol®	67-56-1	200-659-6	32,04 g/mol	CH <sub>4</sub> O

## 3. Hazards Identification

www.rxmarine.com

Signal Word	Danger
Hazard Statements	H225 Highly flammable liquid and vapor. H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled. H370 Causes damage to organs (Eyes, Central nervous system).
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
Classification of the substance or mixture	Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 4. First Aid Measures

www.rxmarine.com

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
Eye Contact	After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Swallowed	After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour)
Skin Contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.
Inhalation	Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delay	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

Flammability	May be combustible at high temperature.
Suitable extinguishing media	Water Foam Carbon dioxide (CO <sub>2</sub> ) Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.
Further information	Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Environmental Precaution	Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up

Reference to other sections

affected area.

For disposal see section 13.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Incompatible materials

Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Conditions for safe storage, including any incompatibilities

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons. Moisture sensitive.

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Advice on general occupational hygiene

Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

Exposure controls

No specific additional engineering controls are required. Provide good natural or artificial ventilation.

Engineering Control

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Body Protection

Flame retardant antistatic protective clothing.

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)). Full contact Material: butyl-rubber Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Butoject® (KCL 898) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)). Splash contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 120 min Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Respiratory protection

Required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system. Recommended Filter type: Filter type AX

Other Protection Measure

Handle in accordance with good industrial hygiene and safety practice.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

## 9. Physical and chemical properties

www.rxmarine.com

Physical state	Liquid
Colour	Colorless
Odour	characteristic
Odor Threshold	Not Applicable
pH	No data available
Melting Point	-97,8 °C - (ECHA)
Boiling Point	64,7 °C at 1.013 hPa - (ECHA)
Flash Point	9,7 °C - closed cup
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	Upper explosion limit: 44 %(V) Lower explosion limit: 5,5 %(V)
Autoignition temperature	455,0 °C at 1.013 hPa - DIN 51794
Decomposition temperature	No data available
Vapour pressure	169,27 hPa at 25 °C
Viscosity	0,54 - 0,59 mm <sup>2</sup> /s at 20 °C
Density	0,79 g/cm <sup>3</sup> at 20 °C
Relative Density	0,79 - 0,8 at 20 °C
Specific Gravity	No data available
Partition coefficient	log Pow: -0,77 -
Explosive properties	No data available
Solubility	1.000 g/l at 20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

## 10. Stability and reactivity

www.rxmarine.com

Reactivity	Vapors may form explosive mixture with air.
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Risk of explosion with: Oxidizing agents perchloric acid perchlorates salts of oxyhalogenic acids chromium(VI) oxide halogen oxides nitrogen oxides nonmetallic oxides chromosulfuric acid chlorates hydrides zinc diethyl halogens powdered magnesium hydrogen peroxide Nitric acid sulfuric acid permanganic acid sodium hypochlorite Exothermic reaction with: acid halides Acid anhydrides Reducing agents acids Bromine Chlorine Chloroform magnesium tetrachloromethane Risk of ignition or formation of inflammable gases or vapours with Fluorine
Conditions to avoid	Warming.
Incompatible materials	various plastics, magnesium, zinc alloys
Hazardous decomposition products	In the event of fire: see section 5

## 11. Toxicological information

www.rxmarine.com

Acute toxicity	Acute toxicity estimate Oral - 100,1 mg/kg (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Symptoms: Nausea, Vomiting Acute toxicity estimate Inhalation - 4 h - 3,1 mg/l - vapor (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Symptoms: Irritation symptoms in the respiratory tract. Acute toxicity estimate Dermal - 300,1 mg/kg (Expert judgment) Remarks: Classified according
----------------	--

Skin corrosion/irritation	to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Skin - Rabbit Result: No skin irritation Remarks: (ECHA) Remarks: Drying-out effect resulting in rough and chapped skin.
Serious eye damage/irritation	Eyes - Rabbit Result: No eye irritation Remarks: (ECHA)
Respiratory or skin sensitization	Sensitisation test: - Guinea pig Result: negative (OECD Test Guideline 406)
Carcinogenicity	Did not show carcinogenic effects in animal experiments.
Germ cell mutagenicity	Based on available data the classification criteria are not met. Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation
Reproductive toxicity	Based on available data the classification criteria are not met.
Specific target organ toxicity - single exposure	Causes damage to organs. - Eyes, Central nervous system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Additional Information	RTECS: UF9625000 Lung irritation, Cyanosis, Central nervous system depression To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

Persistence and degradability	No data available
Toxicity to fish	Flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15.400,0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - Daphnia magna (Water flea) - 18.260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity	Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 1.520 mg/l - 96 h
Toxicity to bacteria	static test IC50 - activated sludge - > 1.000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca. 22.000,0 mg/l - 96 h (OECD Test Guideline 201)
Products Biodegradation	The methods for determining the biological degradability are not applicable to inorganic substances.
Mobility in soil	Will not adsorb on soil.
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	No data available
Other adverse effects	No data available .

## 13. Disposal considerations

[www.rxmarine.com](http://www.rxmarine.com)

Waste treatment Method	No data available
------------------------	-------------------

## 14. Transport information

[www.rxmarine.com](http://www.rxmarine.com)

UN number	ADR/RID:1230 IMDG:1230 IATA: 1230
UN proper shipping name	ADR/RID:METHANOL IMDG:METHANOL IATA:METHANOL
Transport hazard class(es)	ADR/RID: 3 (6.1) IMDG: 3 (6.1) IATA:3 (6.1)
Packaging group	ADR/RID: II IMDG: II IATA:II
Environmental hazards	ADR/RID: No IMDG: No IATA: No
Special precautions for user	No data available
Further information	Not classified as dangerous in the meaning of transport regulations.

## 15. Regulatory information

[www.rxmarine.com](http://www.rxmarine.com)

Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.

Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

## 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

**DISCLAIMER OF LIABILITY** :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.