

## 1. Product and Company Identification

www.rxmarine.com

Product Name Methyl ester of acrylic acid (methyl acrylate)  
Part Number RXSOL-19-1213-240

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400  
Fax +91 22 27612100 ::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmarine.com](http://www.rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Cas No	EC No	Whight	Formula
Methyl acrylate (stabilised with hydroquinone monomethyl ether) for synthesis	96-33-3	202-500-6	86,09 g/mol	C <sub>4</sub> H <sub>6</sub> O <sub>2</sub>

## 3. Hazards Identification

www.rxmarine.com

Signal Word	Danger
Hazard Statements	H300 + H310 Fatal if swallowed or in contact with skin.
Precautionary statements	P262 Do not get in eyes, on skin, or on clothing. P280 Wear protective gloves/ protective clothing. P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth. P302 + P352 + P310 IF ON SKIN: Wash with plenty of water. Immediately call a POISON CENTER/ doctor.
Classification of the substance or mixture	Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 4. First Aid Measures

www.rxmarine.com

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
Eye Contact	After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.
Swallowed	After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Skin Contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
Inhalation	Fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

Flammability	May be combustible at high temperature.
Suitable extinguishing media	Carbon dioxide (CO <sub>2</sub> ) Foam Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.
Further information	Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Environmental Precaution	Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.
Reference to other sections	For disposal see section 13.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

Advice on protection against fire and explosion	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Advice on safe handling	Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.
Conditions for safe storage, including any incompatibilities	Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons. Moisture sensitive.
Storage conditions	Protected from light. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons. Recommended storage temperature see product label.
Storage class	Storage class (TRGS 510): 3: Flammable liquids
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

Exposure controls	No specific additional engineering controls are required. Provide good natural or artificial ventilation.
Engineering Control	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses
Body Protection	Flame retardant antistatic protective clothing.
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: <a href="http://www.kcl.de">www.kcl.de</a> ). Full contact Material: butyl-rubber Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Butoject® (KCL 898) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: <a href="http://www.kcl.de">www.kcl.de</a> ). Splash contact Material: Nitrile rubber Minimum layer thickness: 0,4 mm Break through time: 30 min Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)
Respiratory protection	Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Control of environmental exposure	Do not let product enter drains. Risk of explosion.

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

Physical state	Liquid
----------------	--------

Colour	Colorless
Odour	pungent
Odor Threshold	Not Applicable
pH	at 20 °C
Melting Point	-76,5 °C
Boiling Point	80,1 °C at 1.013 hPa
Flash Point	-2,8 °C - closed cup
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	Upper explosion limit: 25 %(V) Lower explosion limit: 2,8 %(V)
Autoignition temperature	468 °C at 1.013,25 hPa
Decomposition temperature	No data available
Vapour pressure	90 hPa at 20,2 °C 150 hPa at 30,8 °C
Viscosity	Viscosity, kinematic: 10 mm <sup>2</sup> /s at 23 °C Viscosity, dynamic: 0,472 mPa.s at 25 °C
Density	0,96 g/cm <sup>3</sup> at 20 °C
Relative Density	0,95 at 20 °C
Specific Gravity	No data available
Partition coefficient	log Pow: 0,74 at 25 °C
Explosive properties	No data available
Solubility	ca.60 g/l at 20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

## 10. Stability and reactivity

[www.rxmarine.com](http://www.rxmarine.com)

Reactivity	Vapors may form explosive mixture with air.
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature) . Contains the following stabilizer(s): hydroquinone monomethyl ether (0,01 %)
Possibility of hazardous reactions	Risk of explosion with: Peroxides Strong oxidizing agents Strong acids strong alkalis Activated charcoal
Conditions to avoid	Heat. May polymerize on exposure to light. Warming.
Incompatible materials	Strong acids, Strong bases, Strong oxidizing agents, Strong reducing agents
Hazardous decomposition products	In the event of fire: see section 5

## 11. Toxicological information

[www.rxmarine.com](http://www.rxmarine.com)

Acute toxicity	Acute toxicity estimate Oral - 768,08 mg/kg (Calculation method) LD50 Oral - Rat - male - 768 mg/kg (OECD Test Guideline 401) Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract. Acute toxicity estimate Inhalation - 4 h - 3 mg/l - vapor(Calculation method) LC50 Inhalation - Rat - male and female - 4 h - 6,5 mg/l - vapor (OECD Test Guideline 403) Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract Acute toxicity estimate Dermal - 1.251 mg/kg (Calculation method) LD50 Dermal - Rabbit - 1.250 mg/kg Remarks: (ECHA)
Skin corrosion/irritation	Skin - Rabbit Result: irritating - 4 h (OECD Test Guideline 404)
Serious eye damage/irritation	Eyes - Rabbit Result: Eye irritation Remarks: (IUCLID)
Respiratory or skin sensitization	Local lymph node assay (LLNA) - Mouse Result: positive (OECD Test Guideline 429)

Carcinogenicity	No data available
Germ cell mutagenicity	Test Type: Ames test Result: Not mutagenic in Ames Test. Remarks: (IUCLID)
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Additional Information	RTECS: UF9625000 Lung irritation, Cyanosis, Central nervous system depression To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

Persistence and degradability	No data available
Toxicity to fish	Flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 3,4 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	flow-through test EC50 - Daphnia magna (Water flea) - 2,6 mg/l - 48 h (OECD Test Guideline 202)
Toxicity	Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 1.520 mg/l - 96 h
Toxicity to bacteria	static test EC10 - activated sludge - > 100 mg/l - 72 h Remarks: (ECHA)
Toxicity to algae	Static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 74,35 mg/l - 72 h (OECD Test Guideline 201) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: maleic acid
Products Biodegradation	The methods for determining the biological degradability are not applicable to inorganic substances.
Mobility in soil	No data available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	No data available
Other adverse effects	No data available .

## 13. Disposal considerations

[www.rxmarine.com](http://www.rxmarine.com)

Product	Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	See <a href="http://www.retrologistik.com">www.retrologistik.com</a> for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

## 14. Transport information

[www.rxmarine.com](http://www.rxmarine.com)

UN number	ADR/RID:1919 IMDG:1919 IATA:1919
UN proper shipping name	ADR/RID:METHYL ACRYLATE, STABILIZED IMDG:METHYL ACRYLATE, STABILIZED IATA:METHYL ACRYLATE, STABILIZED
Transport hazard class(es)	ADR/RID: 3 IMDG: 3 IATA:3
Packaging group	ADR/RID: II IMDG: II IATA:II
Environmental hazards	ADR/RID: No IMDG: No IATA: No
Special precautions for user	No data available

## 15. Regulatory information

[www.rxmarine.com](http://www.rxmarine.com)

Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.

Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

## 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

**DISCLAIMER OF LIABILITY** :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.