

## 1. Product and Company Identification

www.rxmarine.com

Product Name                   RXSOL-19-1179-025  
Product Type                   ETHYLENE DIAMINE

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point ::: Kandla, Kolkata, Chennai, Visakhapatnam, Mumbai, Fujairah

Phone                           +91 22 27815540 / 41 / 42  
Fax                               +91 22 2781 1318 :::AOH :0091 9821214367  
Email                           [mail@rxmarine.com](mailto:mail@rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Chemica Name	Concentration	CAS Number
Ethylenediamine	60-100%	107-15-3

\*See Section 16

## 3. Hazards Identification

www.rxmarine.com

Odour	Smells of hydrocarbon.
Appearance	Appearance: Colorless, viscous liquid Danger! Causes eye and skin burns. Causes digestive and respiratory tract irritation. May cause allergic respiratory and skin reaction. Harmful if absorbed through the skin. May be harmful if inhaled. Hygroscopic (absorbs moisture from the air).
Contactwith eyes Contact with skin	Causes irritation.  Harmful if absorbed through the skin. Causes skin burns. May cause skin sensitization, an allergic reaction, which upon re-exposure to this material. Undiluted EDA is corrosive to rabbit skin, causing complete tissue destruction after 14 days. Vapours may cause drowsiness and dizziness (R67), In cases of severe exposure, anaesthesia may develop, In cases of chronic pneumonitis may develop.
Inhalation	Vapours may cause drowsiness and dizziness (R67), In cases of severe exposure, anaesthesia may develop, In cases of chronic pneumonitis may develop.
Ingestion	Ingestion: Causes gastrointestinal tract burns. May cause liver and kidney damage. May be harmful if swallowed. Inhalation: Causes severe allergic respiratory reaction. Irritation may lead to chemical pneumonitis and pulmonary edema. May cause skin damage. Causes chemical burns to the respiratory tract. May cause asthma. Chronic: May cause liver and kidney damage. Exposure may cause allergic respiratory reaction (asthma).
General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

## 4. First Aid Measures

www.rxmarine.com

Contact with skin	Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash thoroughly before reuse.
Contact with eyes Ingestion	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid. Call a poison control center. If swallowed, do not induce vomiting unless directed to do so by medical personnel. Do not give anything by mouth to an unconscious person. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. Notes to Physician: Treat symptomatically and supportively.
General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

## 5. Fire-fighting Measures

www.rxmarine.com

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, thermal decomposition or combustion may generate irritating and highly toxic gases.

Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor.

Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Extinguishing Media: Solid streams of water may be ineffective and spread material.

Use water spray, dry chemical, "alcohol resistant" foam, or carbon dioxide.

Autoignition Temperature: Not applicable.

Flash Point: Not applicable.

NFPA Rating: (estimated) Health: 3; Flammability: 3; Instability: 0 Explosion Limits: Lower: n/a Upper: n/a

## 6. Accidental Release Measures

www.rxmarine.com

Personal Precautions	Wear protective clothing as per section 8. General Information: Use proper personal protective equipment as indicated in section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container.
Environmental Precautions	Do not allow to enter public sewers and watercourses.
Immediate Actions	Use appropriate containment to avoid environmental contamination (S57).
Clean Up Actions	Absorb spillage in inert material and shovel up. Ventilate the area and wash spill site after material pick-up is complete.
Special Precautions	Wear protective clothing as per section 8. Vapours are heavier than air and may travel considerable distances to a source of ignition. flashback Wear suitable respiratory protection.

Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. Evacuate unnecessary personnel. Approach spill from upwind. Use water spray to cool and disperse vapors, protect personnel, and dilute spills to form nonflammable mixtures

## 7. Handling and Storage


www.rxmarine.com

Handling	Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers and equipment. Use spark-proof tools and explosion proof equipment. Do not get in eyes, on skin, or on clothing. Empty product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, open flames, sparks, or fire. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Do not use compressed air for cleaning. Do not use water spray or mist. Use only with adequate ventilation or respiratory protection.
Storage	Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, wellventilated area. Do not store with incompatible substances. Flammables-area. Store protected from moisture. Do not store in copper or copper alloy storage containers. Keep container tightly closed, in a cool, well ventilated place (S3/7/9).Keep away from open flames, hot surfaces, and sources of ignition.

## 8. Exposure controls and personal protection

www.rxmarine.com

Exposure Limits	OSHA Vacated PELs: Ethylenediamine: 10 ppm TWA; 25 mg/m3 TWA
Exposure controls	Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels.
Occupational exposure controls	Wear suitable protective clothing, including eye/face protection and gloves (neoprene or nitrile are recommended). Additional protection may be required under exceptional circumstances when excessive air contamination exists. We are not aware of any known occupational exposure likely to exceed MEL/OES



Respirator

Gloves

Goggles

Suit

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

Odour	Smells Ammonia-like
Appearance	Liquid, colourless, soluble in water
pH	11.9 (25% aq soln)
Vapor Pressure	Not available
Vapor Density	Not available
Freezing/Melting Point	Not available
Evaporation Rate	Not available
Decomposition Temperature	Not available
Boiling Point	Not available
Viscosity	Not available

Solubility in water: Soluble Specific Gravity/Density: Not available Molecular Formula: Not applicable Molecular Weight: Not applicable

## 10. Stability and reactivity

[www.rxmarine.com](http://www.rxmarine.com)

- This article is considered stable under normal conditions.
- Avoid overheating, Keep away from naked flames, incandescent or hot surfaces.

Chemical Stability: Absorbs carbon dioxide from air to form nonvolatile carbonate. Conditions to Avoid: Incompatible materials, ignition sources, excessive heat, confined spaces. Incompatibilities with Other Materials: Strong oxidizing agents, strong acids, copper, copper alloys. Hazardous Decomposition Products: Nitrogen oxides, carbon monoxide, carbon dioxide, ammonia and/or derivatives. Hazardous Polymerization: Has not been reported.

## 11. Toxicological information

[www.rxmarine.com](http://www.rxmarine.com)

Toxicological information	RTECS: CAS# 107-15-3: KH8575000. CAS# 7732-18-5: ZC0110000. LD50/LC50: CAS# 107-15-3: Draize test, r Severe; Draize test, rabbit, eye: 750 ug/24H Severe; Inhalation, mouse: LC50 = 300 mg/m <sup>3</sup> ; Oral, mouse: LD50 = 1200 mg/kg; Skin, rabbit: LD50 = 730 uL/kg CAS# 7732-18-5: Oral, rat: LD50 = >90 mL/kg
Inhalation	Epidemiology: Edema of the epithelium of the cornea, generally without pain, has been produced by amine vapor haloes to be seen around lights, usually in the evening, after industrial exposure to the vapors of various amines.
Contact with skin	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.
Contact with eyes	In cases of severe exposure, irritation may develop.
Ingestion	May cause gastro-intestinal disturbances. Aspiration hazard Harmful: may cause lung damage if swallowed (R65).
Carcinogenicity	Carcinogenicity: CAS# 107-15-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 7732-18-5: Not listed by NTP, or CA Prop 65.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

Ecotoxicity	Ecotoxicity: Fish: Fathead Minnow: LC50 = 115.7 mg/L; 96 Hr.; Static Condition Fish: Rainbow trout: LC50 = 23 mg/L; Static Condition Water flea EC50 = 0.88 mg/L; 48 Hr.; Unspecified Bacteria: Phytobacterium phosphoreum: EC50 = 0.1 mg/L; Minutes; Microtox test Chub (fresh water) 60ppm/24H (lethal) Rainbow trout LC50=230 mg/L/48H
Mobility	Insoluble in water.
Persistence and Biodegradability	Biodegradability 67 % (OECD 301F).
Bioaccumulation Potential	Low bioaccumulation potential.
Adverse Effects	Environmental: On soil, substance will leach and volatilize. In water, substance will form alkaline solution and

Bioconcentration is not predicted. In air, substance will react with hydroxyl radicals and carbon dioxide. Biological (BOD): 75% (theory), 5 days

### 13. Disposal considerations

[www.rxmarine.com](http://www.rxmarine.com)

Classification	EU Waste class: 07.01. Dispose of in accordance with Federal, State, and local regulations
Disposal considerations	Do not discharge into drains or the environment, dispose to an authorised waste collection point Disposal should be in accordance with local, state or national legislation.

### 14. Transport information

[www.rxmarine.com](http://www.rxmarine.com)

US DOT Shipping Name: ETHYLENEDIAMINE Hazard Class: 8 UN Number: UN1604 Packing Group: II

### 15. Regulatory information

[www.rxmarine.com](http://www.rxmarine.com)

Risk Phrases	Harmful: may cause lung damage if swallowed (R65). Repeated exposure may cause skin dryness or cracking (R66)
Safety Phrases	Do not breathe vapour/fumes (S23) Avoid contact with skin (S24) Wear suitable gloves and eye/face protection (S37) Do not induce vomiting; seek medical advice immediately and show this container or label (S62).

### 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

Text of R and S phrase codes used in this safety data sheet:- R65: Harmful: may cause lung damage if swallowed; R66: Repeated exposure may cause skin dryness or cracking. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet Do not use for other application(s) without seeking advice from manufacturer.

This Safety Data Sheet is provided in compliance with The Dangerous Substances Directive

This Safety Data Sheet is provided in compliance with The Dangerous Preparations Directive

This Safety Data Sheet is provided in compliance with The Safety Data Sheets Directive

**DISCLAIMER OF LIABILITY** :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.