

1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-19-1181-025
Product Type ETHYLENE DI CHLORIDE EDC

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kolkata, Chennai, Gandhidham, Visakhapatnam, Fujairah, Muscat

Phone +91 22 27815541 / 42
Fax +91 22 2781 1318 ::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Ingredient	CAS No	Percent
1,2-Dichloroethane	107-06-2	99.9+%

3. Hazards Identification

www.rxmarine.com

Highly flammable. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause cancer.

Eye: Causes severe eye irritation. Contact with liquid or vapor causes severe burns and possible irreversible eye damage. Causes eye pain.

Skin: Causes mild skin irritation. May be absorbed through the skin. Causes redness and pain.

Ingestion: Harmful if swallowed. May cause central nervous system depression, kidney damage, and liver damage. May cause gastric irritation with nausea, vomiting and diarrhea. May cause effects similar to those for inhalation exposure.

Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause liver and kidney damage.

Chronic: Prolonged or repeated skin contact may cause dermatitis. Prolonged or repeated eye contact may cause conjunctivitis, and kidney damage.

4. First Aid Measures

www.rxmarine.com

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids immediately.

Skin: Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Ingestion: If victim is conscious and alert, give 2-4 cupfuls of milk or water. Get medical aid immediately.

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial breathing is difficult, give oxygen.

5. Fire-fighting Measures

www.rxmarine.com

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors can travel to a source of ignition and flash back

Extinguishing Media: For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective.

6. Accidental Release Measures

www.rxmarine.com

General Information:	Use proper personal protective equipment as indicated in Section 8.
Spills/Leaks:	Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition and use a spark-proof tool.

7. Handling and Storage

www.rxmarine.com

Handling	Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use only in a well-ventilated area with adequate ventilation. Do not get on skin and clothing. Keep container tightly closed. Keep away from heat, sparks and open flames. Do not ingest or inhale. Use only in a chemical fume hood.
Storage:	Keep away from heat, sparks, and flame. Store in a tightly closed container. Keep under a nitrogen blanket. Keep from contact with oxidizing materials. Store in a cool, dry, wellventilated area away from incompatible substances. Flammables-area.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Controls	Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Provide adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.
Exposure Limits	CAS# 107-06-2: United Kingdom, WEL - TWA: 5 ppm TWA; 21 mg/m ³ TWA United Kingdom, WEL - STEL: 15 ppm STEL mg/m ³ STEL United States OSHA: 50 ppm TWA; 100 ppm Ceiling Belgium - TWA: 10 ppm VLE; 41 mg/m ³ VLE Netherlands: 5 ppm VME; 40 mg/m ³ VME Germany: 5 ppm TWA; 20 mg/m ³ TWA Japan: 10 ppm OEL; 40 mg/m ³ OEL Malaysia: 40 mg/m ³ TWA Netherlands: 1.5 ppm MAC; 7 mg/m ³ MAC Russia: 10 mg/m ³ TWA (vapour) Spain: 5 ppm VLA-ED
Personal Protective Equipment	Eyes: Wear chemical splash goggles. Skin: Wear appropriate protective gloves to prevent skin exposure. Clothing: Wear appropriate protective clothing to prevent skin exposure. Respirators: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a respirator or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

9. Physical and chemical properties

www.rxmarine.com

Physical State:	Clear liquid
Color:	colorless
Odor:	chloroform-like
pH:	Not available
Vapor Pressure:	65mmHg @29 deg C
Viscosity:	0.8 mPas @20 deg C
Boiling Point:	81 - 85 deg C @760mmHg
Freezing/Melting Point:	-35 deg C (-31.00°F)
Autoignition Temperature:	440 deg C (824.00 deg F)
Flash Point:	13 deg C (55.40 deg F)
Explosion Limits: Lower:	6.2 Vol %
Explosion Limits: Upper:	15.9 Vol %
Decomposition Temperature:	Not available

Solubility in water: 8.7 g/l (20°C)

Specific Gravity/Density: 1.250

Molecular Formula: C2H4Cl2

Molecular Weight: 98.96

10. Stability and reactivity

www.rxmarine.com

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Incompatible materials, light, ignition sources, excess heat, electrical sparks.

Incompatibilities with Other Materials Strong oxidizing agents, reducing agents, bases, alkali metals, aluminum, liquid ammonia, nitric acid, organic peroxides.

Hazardous Decomposition Products Hydrogen chloride, carbon monoxide, carbon dioxide.

Hazardous Polymerization Will not occur.

11. Toxicological information

www.rxmarine.com

RTECS#: CAS# 107-06-2: KI0525000

LD50/LC50: RTECS:

CAS# 107-06-2: Draize test, rabbit, eye: 63 mg Severe; Draize test, rabbit, eye: 500 mg/24H Mild; Draize test, rabbit, skin: 500 mg/24H Mild; Inhalation, mouse: LC50 = 1060 mg/m³/6H; Inhalation, rat: LC50 = 1000 ppm/7H; Inhalation, rat: LC50 = 5100 mg/m³/6H; Oral, mouse: LD50 = 413 mg/kg; Oral, mouse: LD50 = 413 mg/kg; Oral, rabbit: LD50 = 860 mg/kg; Oral, rabbit: LD50 = 0.7 mL/kg; Oral, rat: LD50 = 500 mg/kg; Skin, rabbit: LD50 = 2800 mg/kg; Other: Skin, rabbit: 625 mg mild

Carcinogenicity: 1,2-Dichloroethane - California: carcinogen, initial date 10/1/87 NTP: Suspect carcinogen IARC: Group 2B carcinogen

Other: See actual entry in RTECS for complete information.

12. Ecological information

www.rxmarine.com

Ecotoxicity: Not available

13. Disposal considerations

www.rxmarine.com

Dispose of in a manner consistent with federal, state, and local regulations

14. Transport information

www.rxmarine.com

Proper Shipping Name:	ETHYLENE DICHLORIDE	
UN NO.	1184	
Hazard Class	3	PackingGroup
Proper Shipping Name	ETHYLENE DICHLORIDE	
ADR UN No.	1184	
ADR Hazard Class	3	
Proper Shipping Name	ETHYLENE DICHLORIDE	
IMDG UN No.	1184	
IMDG Hazard Class	3	IMDG PackGroup.:

15. Regulatory information

www.rxmarine.com

European/International Regulations :

European Labeling in Accordance with EC Directives

Hazard Symbols: T F

Risk Phrases:

R 45 May cause cancer.

R 11 Highly flammable.

R 22 Harmful if swallowed.

R 36/37/38 Irritating to eyes, respiratory system and skin.

Safety Phrases:

S 53 Avoid exposure - obtain special instructions before use.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). WGK (Water Danger/Protection)

CAS# 107-06-2: 3 Canada

CAS# 107-06-2 is listed on Canada's DSL List US Federal

TSCA

CAS# 107-06-2 is listed on the TSCA Inventory.

16. Other information

www.rxmarine.com

The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.