

1. Product and Company Identification

www.rxmarine.com

Product Name Natural Graphite Powder C 80
Part Number RXSOL-92-0655-035

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Substances

Synonyms Graphite grade 3061
Formula C
Molecular weight 12,01 g/mol
CAS-No 7782-42-5
EC-No. 231-955-3

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Label elements Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008
Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

If inhaled If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact Wash off with soap and plenty of water.

In case of eye contact Flush eyes with water as a precaution.

If swallowed Never give anything by mouth to an unconscious person. Rinse mouth with water.

Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed No data available

Extinguishing media

Suitable extinguishing media

Special hazards arising from the substance or mixture

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Carbon oxides

Advice for firefighters

Further information

Wear self-contained breathing apparatus for firefighting if necessary.

No data available

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk.
Use water

spray to keep fire-exposed containers cool.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapors, mist or gas.

Environmental precautions

For personal protection see section 8.

Methods and materials for containment and cleaning up

No special environmental precautions required.

Reference to other sections

Sweep up and shovel. Keep in suitable, closed containers for disposal.

For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Provide appropriate exhaust ventilation at places where dust is formed.

Conditions for safe storage, including any incompatibilities

General industrial hygiene practice.

For precautions see section 2.2.

Recommended storage temperature see product label. Tightly closed.

Specific end use(s)

Recommended storage temperature see product label.

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Ingredients with workplace control parameters

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet,

supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet,

supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following

standards: DIN EN 143, DIN 14387 and other accompanying standards relating to

the used respiratory protection system.

Recommended Filter type: Filter type P1

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory

protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Do not let product enter drains..

Respiratory protection

Control of environmental exposure

9. Physical and chemical properties

www.rxmarine.com

Information on basic physical and chemical properties

Physical state

Powder

Color

Dark gray

Odor	Odorless
Melting point/freezing point	Melting point: 400 °C
Initial boiling point and boiling range	205,7 °C at 977,6 hPa - OECD Test Guideline 103
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	No data available
Flash point	138,6 °C - closed cup
Autoignition temperature	360 °C
Decomposition temperature	No data available
	materials. Extremely flammable in the presence of the following materials or conditions: oxidizing
	materials.
pH	No data available
Viscosity	Viscosity, kinematic: No data available
	Viscosity, dynamic: No data available
Water solubility	256,084 g/l at 25 °C - OECD Test Guideline 105- completely soluble
Partition coefficient: n-octanol/water	log Pow: -0,698 at 30 °C - Bioaccumulation is not expected., (ECHA)
Vapor pressure	< 0,1 hPa at 20 °C
Density	1,116 g/cm ³ at 20 °C at 975,5 hPa - OECD Test Guideline 109
Relative density	No data available
Relative vapor density	No data available
Particle characteristics	No data available
Explosive properties	No data available
Oxidizing properties	None
Other safety information	
Bulk density	400 - 500 kg/m ³

10. Stability and reactivity

www.rxmarine.com

Reactivity	No data available
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	No data available
Conditions to avoid	No data available
Incompatible materials	No data available
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

www.rxmarine.com

Information on toxicological effects

Acute toxicity	LD50 Oral - Rat - female - > 2.000 mg/kg (OECD Test Guideline 423)
	LC50 Inhalation - Rat - male and female - 4 h - 2.000 mg/m ³ - dust/mist (OECD Test Guideline 403)
	Dermal: No data available
Skin corrosion/irritation	Skin - Rabbit Result: No skin irritation

(OECD Test Guideline 404)

- Mouse

Did not cause sensitization on laboratory animals.

(OECD Test Guideline 429)

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks:

(in analogy to similar products)

Test Type: Micronucleus test

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Disodium molybdate dihydrate

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Disodium molybdate dihydrate

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Disodium molybdate dihydrate

No data available

No data available

No data available

No data available

No data available

Serious eye damage/eye irritation

Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

Aspiration hazard

12. Ecological information

www.rxmarine.com

Toxicity

Toxicity to fish

Semi-static test LC50 - Danio rerio (zebra fish) - > 100 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

Static test EC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae

Static test EC50 - Pseudokirchneriella subcapitata - > 100 mg/l - 72 h

(OECD Test Guideline 201)

13. Disposal considerations

www.rxmarine.com

Waste treatment Method

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

www.rxmarine.com

UN number

ADR/RID:2404 IMDG:2404 IATA: 2404

UN proper shipping name

ADR/RID:PROPIONITRILE
IMDG:PROPIONITRILE IATA:PROPIONITRILE

Transport hazard class(es)

ADR/RID: 3 (6.1) IMDG: 3 (6.1) IATA:3 (6.1)

Packaging group

ADR/RID: II IMDG: II IATA:II

Environmental hazards

ADR/RID: No IMDG: No IATA: No

Special precautions for user

No data available

Further information

Not classified as dangerous in the meaning of transport regulations.

15. Regulatory information

www.rxmarine.com

Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.

Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

16. Other information

www.rxmarine.com

Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the

information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.