

## 1. Product and Company Identification

www.rxmarine.com

Product Name Metal Polishing  
Part Number RXSOL-16-3742-005

Company Details:....

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400  
Fax +91 22 27612100 ::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmarine.com](http://www.rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

### Substances

Ingredient name	Classification	Concentration
Pumice	?1 - ?5	1332-09-8
propan-2-ol	?1 - ?5	67-63-0
Index-No. CAS-No.		
EC-No.		
Index-No.		
ammonia	?1 - ?5	1336-21-6

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 3. Hazards Identification

www.rxmarine.com

### Classification of the substance or mixture

Classification of the substance or mixture  
FLAMMABLE LIQUIDS - Category 3  
EYE IRRITATION - Category 2B

### GHS label elements

Signal word Warning  
Hazard Statements Flammable liquid and vapor.  
Causes eye irritation.

### Precautionary statements

General Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention Wear protective gloves. Wear eye or face protection. Keep away from

Response	heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosionproof electrical, ventilating, lighting and all material-handling equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling.
Storage	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Disposal	Store in a well-ventilated place. Keep cool.
Supplemental label elements	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	None known.

## 4. First Aid Measures

[www.rxmarine.com](http://www.rxmarine.com)

### Description of first aid measures

Eye contact	Consult a physician. Show this material safety data sheet to the doctor in attendance.
Inhalation	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.
Ingestion	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Most important symptoms/effects, acute and delayed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Potential acute health effects	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Eye contact	Causes eye irritation.
Inhalation	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	Adverse symptoms may include the following:  irritation  watering  redness
Inhalation	No specific data
Skin contact	No specific data
Ingestion	No specific data
Indication of immediate medical attention and special treatment needed, if necessary	
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed.  The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### Extinguishing media

Suitable extinguishing media

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide

carbon monoxide

nitrogen oxides

metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

### Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not

ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Conditions for safe storage, including any incompatibilities

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## 9. Physical and chemical properties

www.rxmarine.com

### Appearance

Physical state	Liquid. [Viscous liquid.]
Colour	Opaque. Light tan.
Odor	Ammoniacal.
Odor threshold	Not available
pH	9.6 to 10.2
Melting point	Not available
Boiling point	Not available
Flash point	Closed cup: 40.56 to 43.33°C (105 to 110°F)
Evaporation rate	Not available.
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.104 to 1.14
Solubility	<b>materials.</b> Extremely flammable in the presence of the following materials or conditions: oxidizing
Partition coefficient: noctanol/water	<b>materials.</b>
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Dynamic (room temperature): 8000 to 11000 mPa·s (8000 to 11000 cP)

## 10. Stability and reactivity

www.rxmarine.com

<b>Reactivity</b>	No specific test data related to reactivity available for this product or its ingredients
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

www.rxmarine.com

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-

	LD50 Oral	Rat	5000 mg/kg	
ammonia	LD50 Oral	Rat	350 mg/kg	-
Conclusion/Summary	Based on available data, the classification criteria are not met.			

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
propan-2-ol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit		10 milligrams	
	Eyes - Severe irritant	Rabbit		100 milligrams	
ammonia	LD50 Oral	Rat	350 mg/kg		

### Conclusion/Summary

Skin	Based on available data, the classification criteria are not met.
Eyes	Based on Calculation Method: Causes serious eye irritation
Respiratory	Based on available data, the classification criteria are not met.
Sensitization	Not available.
Conclusion/Summary	
Skin	Based on available data, the classification criteria are not met.
Respiratory	Based on available data, the classification criteria are not met.
Mutagenicity	Not available.
Conclusion/Summary	Based on available data, the classification criteria are not met.
Carcinogenicity	Not available.
Conclusion/Summary	Based on available data, the classification criteria are not met.

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

### Toxicity

Product/ingredient name	Result	Species	Exposure
propan-2-ol	Acute EC50 10100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours

### Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propan-2-ol	0.05		low
Mobility in soil			
Soil/water partition coefficient (KOC)		Not available.	
Other adverse effects		No known significant effects or critical hazards.	

## 13. Disposal considerations

www.rxmarine.com

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

www.rxmarine.com

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN1993	UN1993	UN1993	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol)
Transport hazard class(es)	3	3	3	3
Packaging group	III	III	III	III
Environmental hazards	No	No	No	No
DOT Classification			Limited Quantity	
TDG Classification			Limited Quantity	
IMDG			Limited Quantity	
IATA			See DG List	
Special precautions for user			Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
Transport in bulk according to Annex II of MARPOL and the IBC Code			Not available.	

## 15. Regulatory information

www.rxmarine.com

U.S. Federal regulations	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed
Clean Air Act Section 602	Not listed

---

Class I Substances

Clean Air Act Section 602

Not listed

Class II Substances

DEA List I Chemicals (Precursor Chemicals)

Not listed

DEA List II Chemicals (Precursor Chemicals)

Not listed

## 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

### Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

**DISCLAIMER OF LIABILITY :**The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.