## 1. Product and Company Identifaction

www.rxmarine.com

Porduct Name Poly quaternium 7 Part Number RXSOL-19-3542-025

Company Details:....

RX MARINE INTERNATIONAL 105, A wing, BSEL, TECH PARK. VASHI ,NEW BOMBAY 400703 INDIA

Branch: Kandla, Mumbai, Chennai, Vizag, Kolkata, UAE, OMAN, CANADA and KENYA

Phone +91 22 20871200 - 1400

Fax +91 22 27612100 :::AOH :0091 9821214367

Email mail@rxmarine.com Website www.rxmraine.com

## 2. Composition / Information on ingredients

www.rxmarine.com

**Mixtures** 

Synonyms P(AAm-co-DADMAC)

No components need to be disclosed according to the applicable regulations. 3. Hazards Identification

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No

1272/2008.

Label elements Not a hazardous substance or mixture according to Regulation (EC) No

1272/2008.

Other hazards This substance/mixture contains no components considered to be either

persistent, bioaccumulative and toxic (PBT), or very persistent and very

bioaccumulative (vPvB) at levels of 0.1% or higher.

### 4. First Aid Measures

www.rxmarine.com

#### **Description of first aid measures**

If inhaled If breathed in, move person into fresh air. If not breathing, give artificial

respiration.

In case of skin contact Wash off with soap and plenty of water. In case of eve contact Flush eyes with water as a precaution.

If swallowed Never give anything by mouth to an unconscious person. Rinse mouth

with water.

The most important known symptoms and effects are described in the Most important symptoms and effects, both acute and delayed

labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment No data available

needed

### 5. Fire-fighting Measures

www.rxmarine.com

#### **Extinguishing media**

Suitable extinguishing media Special hazards arising from the substance or mixture Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Carbon oxides

Nitrogen oxides (NOx)

Hydrogen chloride gas

Advice for firefighters Further information Wear self-contained breathing apparatus for firefighting if necessary. No data available

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk.

Use water

spray to keep fire-exposed containers cool.

### 6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapors, mist or gas.

Environmental precautions

For personal protection see section 8.

Methods and materials for containment and cleaning up

No special environmental precautions required. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

## 7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Conditions for safe storage, including any incompatibilities

For precautions see section 2.2.

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Store in

cool place.

Storage class

Storage class (TRGS 510): 12: Non Combustible Liquids

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are

stipulated

## 8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Ingredients with workplace control parameters

**Exposure controls** 

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU).

Handle with gloves. Gloves must be inspected prior to use. Use proper

glove

removal technique (without touching glove's outer surface) to avoid skin

contact

with this product. Dispose of contaminated gloves after use in accordance

with

applicable laws and good laboratory practices. Wash and dry hands.

Skin protection

The selected protective gloves have to satisfy the specifications of Regulation (EU)

2016/425 and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which

differ from EN 374, contact the supplier of the EC approved gloves. This

recommendation is advisory only and must be evaluated by an industrial hygienist

and safety officer familiar with the specific situation of anticipated use by

customers. It should not be construed as offering an approval for any specific use

scenario.

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

Respiratory protection not required. For nuisance exposures use type OV/AG (US) or type ABEK (EU EN 14387) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

No special environmental precautions required.

**Body Protection** 

**Respiratory protection** 

Control of environmental exposure

# 9. Physical and chemical properties

www.rxmarine.com

Physical state

Colour

No data available

Liquid.

Odor Odor Threshold pH No data available No data available Not available.

**Melting Point**