

1. Product and Company Identification

www.rxmarine.com

Product Name POTASSIUM BROMATE 100%
Part Number RXSOL-19-1309-250

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Cas No	EC No	Weight	Formula
Potassium bromate for analysis (max 0,000001% Hg) EMSURE® ACS,ISO,Reag. Ph Eur	7758-01-2	231-829-8	167,01 g/mol	KBrO ₃

3. Hazards Identification

www.rxmarine.com

Signal Word	Danger
Hazard Statements	H271 May cause fire or explosion; strong oxidizer. H301 Toxic if swallowed. H350 May cause cancer.
Precautionary statements	P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P220 Keep away from clothing and other combustible materials. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
Classification of the substance or mixture	Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

www.rxmarine.com

General advice	Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Call in physician.
Eye Contact	After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses
Swallowed	If swallowed: give water to drink (two glasses at most). Seek medical

	advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible.
Skin Contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.
Inhalation	Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

www.rxmarine.com

Flammability	May be combustible at high temperature.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Hydrogen bromide gas Potassium oxides Not combustible. Fire may cause evolution of: hydrogen bromide Has a fire-promoting effect due to release of oxygen. Ambient fire may liberate hazardous vapours.
Further information	Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Enviromental Precaution	Do not let product enter drains.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.
Reference to other sections	For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Advice on protection against fire and explosion

Incompatible materials

Hygiene measures

Advice on safe handling

Conditions for safe storage, including any incompatibilities

Storage conditions

Storage class

Specific end use(s)

Advice on general occupational hygiene

Keep away from open flames, hot surfaces and sources of ignition.

Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

Work under hood. Do not inhale substance/mixture.

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons. Moisture sensitive.

Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Separately or together with other oxidising substances only and away from sources of ignition and heat. Because of their oxidation potential these products can raise the burning rate of combustible substances substantially or ignite combustible substances on contact with them.

Storage class (TRGS 510): 5.1A: Strongly oxidizing hazardous materials

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.

8. Exposure controls and personal protection

www.rxmarine.com

Exposure controls

Engineering Control

Eye/face protection

Body Protection

Skin protection

Respiratory protection

Other Protection Measure

Control of environmental exposure

No specific additional engineering controls are required. Provide good natural or artificial ventilation.

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

protective clothing

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested: KCL 741 Dermatrill® L

Recommended Filter type: Filter B-(P3) The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Handle in accordance with good industrial hygiene and safety practice.

Do not let product enter drains..

9. Physical and chemical properties

www.rxmarine.com

Physical state

Colour

Odour

Odor Threshold

pH

powder, finecrystalline

off-white

odorless

Not Applicable

5,0 - 9,0 at 50 g/l at 20 °C

Melting Point	409 - 413 °C
Boiling Point	> 425 °C at ca.1.023 hPa -
Flash Point	6 °C - closed cup
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	No data available
Autoignition temperature	No data available
Decomposition temperature	370 °C
Vapour pressure	No data available
Viscosity	No data available
Density	3,13 g/cm ³ at 20,7 °C - OECD Test Guideline 109
Relative Density	3,13 at 20,7 °C - OECD Test Guideline 109
Specific Gravity	No data available
Partition coefficient	No data available
Explosive properties	No data available
Solubility	No data available
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

www.rxmarine.com

Reactivity	No data available
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Risk of explosion with: ammonium compounds arsenic bromates organic combustible substances phosphorus Powdered metals Sulfides sulfur carbon Risk of ignition or formation of inflammable gases or vapours with: semimetals nonmetals nonmetallic halides Reducing agents Exothermic reaction with: selenium Generates dangerous gases or fumes in contact with: acids Violent reactions possible with: sulfuric acid Cyanides
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids, Strong bases, Strong oxidizing agents, Strong reducing agents
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

www.rxmarine.com

Acute toxicity	LD50 Oral - Rat - male and female - 157 mg/kg (OECD Test Guideline 401) Inhalation: No data available Dermal: No data available
Skin corrosion/irritation	Skin - In vitro study Result: non-corrosive (OECD Test Guideline 431)
Serious eye damage/irritation	Eyes - In vitro study Result: slight irritation - 240 min (OECD Test Guideline 437)
Respiratory or skin sensitization	Local lymph node assay (LLNA) - Mouse Result: negative (OECD Test Guideline 429)
Carcinogenicity	Presumed to have carcinogenic potential for humans
Germ cell mutagenicity	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: Positive results were obtained in some in vitro tests.
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Additional Information	RTECS: UF9625000 Lung irritation, Cyanosis, Central nervous system depression To the best of our knowledge, the chemical, physical, and

12. Ecological information

www.rxmarine.com

Persistence and degradability	The methods for determining the biological degradability are not applicable to inorganic substances
Toxicity to fish	Static test LC50 - Oncorhynchus mykiss (rainbow trout) - 75 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h (OECD Test Guideline 202)
Toxicity	Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 1.520 mg/l - 96 h
Toxicity to bacteria	EC10 - Bacteria - 14 mg/l - 72 h Remarks: (Lit.) EC5 - E.coli - 15.000 mg/l Remarks: (Lit.) (maximum permissible toxic concentration)
Toxicity to algae	static test ErC50 - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201) static test NOEC - Desmodesmus subspicatus (green algae) - 31,6 mg/l - 72 h (OECD Test Guideline 201)
Products Biodegradation	The methods for determining the biological degradability are not applicable to inorganic substances.
Mobility in soil	No data available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	No data available
Other adverse effects	No data available .

13. Disposal considerations

www.rxmarine.com

Product	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

www.rxmarine.com

UN number	ADR/RID:1484 IMDG:1484 IATA: 1484
UN proper shipping name	ADR/RID:POTASSIU BROMATE IMDG:POTASSIUM BROMATE IATA:POTASSIUM BROMATE
Transport hazard class(es)	ADR/RID: 5.1 IMDG: 5.1 IATA:5.1
Packaging group	ADR/RID: II IMDG: II IATA:II
Environmental hazards	ADR/RID: No IMDG: No IATA: No
Special precautions for user	No data available
Further information	Not classified as dangerous in the meaning of transport regulations.

15. Regulatory information

www.rxmarine.com

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take

16. Other information

www.rxmarine.com

Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.