

1. Product and Company Identification

www.rxmarine.com

Product Name Carpet Stain Remover C

Part Number RXSOL-15-2635-005

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400

Fax +91 22 27612100 ::AOH :0091 9821214367

Email mail@rxmarine.com

Website www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Mixtures

Component	Classification	Concentration
Methanol		
CAS-No. 67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 50 - < 70 %
EC-No. 200-659-6	STOT SE 1; H225, H301 +	
Index-No. 603-001-00-X	H311 + H331, H370	
Registration number 01-2119433307-44-XXXX		
Propane-1,2-diol		
CAS-No. 57-55-6		>= 20 - < 30 %
EC-No. 200-338-0		
2-[Bis(2-hydroxyethyl)amino]-2-(hydroxymethyl) propane-1,3-diol		
CAS-No. 6976-37-0	Skin Irrit. 2; Eye Irrit. 2A;	>= 1 - < 5 %
EC-No. 230-237-7	STOT SE 3; H315, H319,	
	H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16

Label elements

Signal word

Danger

Hazard Statements

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

H370 Causes damage to organs.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/

physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.

P322 Specific measures (see supplemental first aid instructions on this label).

P330 Rinse mouth.

P361 Remove/ Take off immediately all contaminated clothing.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.
None

Hazards not otherwise classified (HNOC) or not covered by GHS

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed No data available

5. Fire-fighting Measures

www.rxmarine.com

Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may

burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Carbon oxides, Nitrogen oxides (NOx)

Wear self-contained breathing apparatus for firefighting if necessary.

Use water spray to cool unopened containers.

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

Advice for firefighters

Further information

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage, including any incompatibilities

For precautions see section 2.2.

Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully

Specific end use(s)

resealed and kept upright to prevent leakage.

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters**Components with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Headache		
		Nausea		
		Dizziness		
		Eye damage		USA. ACGIH Threshold Limit Values (TLV)
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		
		Danger of cutaneous absorption		
		STEL	250.000000 ppm	
		Headache		
		Nausea		
		Dizziness		
		Eye damage		
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		
		Danger of cutaneous absorption		
		TWA	200.000000 ppm 260.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		USA. NIOSH Recommended Exposure Limits
		ST	250.000000 ppm 325.000000 mg/m3	
		Potential for dermal absorption		
		TWA	200.000000 ppm	USA. Occupational

			260.000000 mg/m3	Exposure Limits	
				(OSHA) - Table Z-1 Limits for Air Contaminants	
			The value in mg/m3 is approximate.		
Propane-1,2-diol	57-55-6	TWA	10.000000 mg/m3	USA. Workplace Environmental Exposure Levels (WEEL)	
Biological occupational exposure limits					
Component	CAS-No	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15.0000	Urine	ACGIH - Biological
			mg/l	Exposure Indices	
				(BEI)	
Remarks		End of shift (As soon as possible after exposure ceases)			
Exposure controls					
Appropriate engineering controls			Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.		
Personal protective equipment					
Eye/face protection			Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).		
Skin protection			Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.		
			Full contact		
			Material: butyl-rubber		
			Minimum layer thickness: 0.3 mm		
			Break through time: 480 min		
			Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)		
			Splash contact		
			Material: Nitrile rubber		
			Minimum layer thickness: 0.4 mm		
			Break through time: 30 min		
			Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)		
			data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:		
			EN374		

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It

should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains

9. Physical and chemical properties

www.rxmarine.com

Appearance

Form: liquid

Odor

Colour: colourless

Odour Threshold

No data available

pH

No data available

Melting point/freezing point

No data available

Initial boiling point and boiling range

No data available

Flammability (solid, gas)

No data available

Flash point

No data available

Evaporation rate

11 °C (52 °F) - closed cup

Upper/lower flammability or explosive limits

No data available

Vapour pressure

No data available

materials. Extremely flammable in the presence of the following materials or conditions: oxidizing

Vapour density

materials.

Relative density

No data available

Water solubility

No data available

Partition coefficient: n-octanol/water

No data available

Auto-ignition temperature

No data available

Decomposition temperature

No data available

Explosive properties

No data available

Oxidizing properties

No data available

Other safety information

No data available

10. Stability and reactivity

www.rxmarine.com

Reactivity

No data available

Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Vapours may form explosive mixture with air.
Conditions to avoid	Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents, Chloroformates
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

www.rxmarine.com

Information on toxicological effects

Acute toxicity	No data available
	Inhalation: No data available
	Dermal: No data available
	No data available
Skin corrosion/irritation	No data available
Serious eye damage/eye irritation	No data available
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	No data available
Carcinogenicity	IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-(3,6-Dihydroxy-2,4,5,7-tetrabromoxanthen-9-yl)-benzoic acid) ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
Reproductive toxicity	No data available
	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional Information	RTECS: Not available Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence (Methanol)

12. Ecological information

www.rxmarine.com

Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
Results of PBT and vPvB assessment	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
Other adverse effects	No data available

13. Disposal considerations

www.rxmarine.com

Waste treatment methods	
Product	Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Contaminated packaging	Dispose of as unused product.

14. Transport information

www.rxmarine.com

DOT (US)	UN number: 1230 Class: 3 Packing group: II Proper shipping name: Methanol
IMDG	Poison Inhalation Hazard: No UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D Proper shipping name: METHANOL
IATA	UN number: 1230 Class: 3 (6.1) Packing group: II Proper shipping name: Methanol

15. Regulatory information

www.rxmarine.com

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

www.rxmarine.com

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary
-------------------	--

damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.