### 1. Product and Company Identifaction

www.rxmarine.com

Porduct Name	Carpet Stain Remover C
Part Number	RXSOL-15-2635-005
Company Details:	
RX MARINE INTERNATIONAL	
105, A wing, BSEL, TECH PARK.	
VASHI,NEW BOMBAY 400703 INDIA	
Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CAN	NADA and KENYA
Phone	+91 22 20871200 - 1400
Fax	+91 22 27612100 ::::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmraine.com

# 2. Composition / Information on ingredients

Mixtures

Component	Classification	Concentration
Methanol		
CAS-No. 67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 50 - < 70 %
EC-No. 200-659-6	STOT SE 1; H225, H301 +	
Index-No. 603-001-00-X	H311 + H331, H370	
Registration number 01-2119433307-44-XXXX	x	
Propane-1,2-diol		
CAS-No. 57-55-6		>= 20 - < 30 %
EC-No. 200-338-0		
2-[Bis(2-hydroxyethyl)amino]-2-(hydroxymethy)propane-1,3-diol	1	
CAS-No. 6976-37-0	Skin Irrit. 2; Eye Irrit. 2A;	>= 1 - < 5 %
EC-No. 230-237-7	STOT SE 3; H315, H319,	
	H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 3. Hazards Identification

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 3), H301

www.rxmarine.com

www.rxmarine.com

	Acute toxicity, Inhalation (Category 3), H331
	Acute toxicity, Dermal (Category 3), H311
	Specific target organ toxicity - single exposure (Category 1), H370
	For the full text of the H-Statements mentioned in this Section, see Section 16
Label elements	
Signal word Hazard Statements	Danger H225 Highly flammable liquid and vapour.
	H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled
Precautionary Statements	H370 Causes damage to organs. P210 Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P233 Keep container tightly closed.
	P240 Ground/bond container and receiving equipment.
	P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
	P242 Use only non-sparking tools.
	P243 Take precautionary measures against static discharge.
	P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
	P264 Wash skin thoroughly after handling.
	P270 Do not eat, drink or smoke when using this product.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
	P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/
	physician.
	P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated
	clothing. Rinse skin with water/ shower.
	P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position
	comfortable for breathing.
	P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
	P322 Specific measures (see supplemental first aid instructions on this label).
	P330 Rinse mouth.
	P361 Remove/Take off immediately all contaminated clothing.

	P363 Wash contaminated clothing before reuse.
	P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for
	extinction.
	P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
	P403 + P235 Store in a well-ventilated place. Keep cool.
	P405 Store locked up.
Hazards not otherwise classified (HNOC) or not covered by GHS	P501 Dispose of contents/ container to an approved waste disposal plant. None

#### 4. First Aid Measures

www.rxmarine.com

www.rxmarine.com

<b>Description</b>	of	first	aid	measures
-				

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
If inhaled	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
In case of skin contact	Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Most important symptoms and effects, both acute and delayed	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment	No data available

needed

#### 5. Fire-fighting Measures

#### Extinguishing media

Suitable extinguishing media Special hazards arising from the substance or mixture Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may

burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Carbon oxides, Nitrogen oxides (NOx) Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary. **Further information** Use water spray to cool unopened containers. spray to keep fire-exposed containers cool.Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

#### 6. Accidental Release Measures www.rxmarine.com Personal precautions, protective equipment and emergency Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure procedures adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8. **Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains Methods and materials for containment and cleaning up Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). **Reference to other sections** For disposal see section 13.

#### 7. Handling and Storage

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

www.rxmarine.com

	For precautions see section 2.2.	
Conditions for safe storage, including any incompatibilities	Keep container tightly closed in a dry and well-ventilated place.	
	Containers which are opened must be carefully	
	resealed and kept upright to prevent leakage.	
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated	
8. Exposure controls and personal protection www.rxmarine.com		
Control parameters		

Components with workplace control parameters

Component Methanol	CAS-No. 67-56-1	Value TWA	Control parameters 200.000000 ppm	Basis USA. ACGIH Threshold
	Remarks	Headache		Limit Values (TLV)
		Nausea		
		Dizziness		
		Eye damage		
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		
		Danger of cutaneous absorption STEL	250.000000 ppm	USA. ACGIH Threshold
			250.000000 ppm	Limit Values (TLV)
		Headache		
		Nausea		
		Dizziness		
		Eye damage		
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		
		Danger of cutaneous absorption		
		TWA	200.000000 ppm 260.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		ST	250.000000 ppm 325.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		TWA	200.000000 ppm	USA. Occupational

				260.000000 mg/m3	Exposure Limits
					(OSHA) - Table Z-1 Limits for Air Contaminants
		The value in n approximate.	ng/m3 is		
Propane-1,2-diol	57-55-6	TWA		10.000000 mg/m3	USA. Workplace Environmental Exposure Levels (WEEL)
Biological occupation	al exposure limits				
Component	CAS-No	Parameters	Value	Biological specim	nen Basis
Methanol	67-56-1	Methanol	15.0000	Urine	ACGIH - Biological
			mg/l		Exposure Indices
					(BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			
Exposure controls					
Appropriate engineer	ing controls			t with skin, eyes and clothing after handling the product.	. Wash hands before breaks and
Personal protective ec Eye/face protection	quipment		Face shield a	nd safety glasses Use equipm	ent for eye protection tested
			and approved (US) or EN 1	l under appropriate governme 66(EU).	nt standards such as NIOSH
Skin protection				gloves. Gloves must be inspec l technique (without	ted prior to use. Use proper
				ve's outer surface) to avoid sk ontaminated gloves after	in contact with this product.
			use in accord Wash and dry	ance with applicable laws and y hands.	l good laboratory practices.
			Full contact		
			Material: but	yl-rubber	
			Minimum lay	ver thickness: 0.3 mm	
			Break throug	h time: 480 min	
			Material teste	ed:Butoject® (KCL 897 / Ald	lrich Z677647, Size M)
			Splash contac	st	
			Material: Nit	rile rubber	
			Minimum lay	ver thickness: 0.4 mm	
			Break throug	h time: 30 min	
			Material teste	ed:Camatril® (KCL 730 / Ald	lrich Z677442, Size M)
				KCL GmbH, D-36124 Eicher l sales@kcl.de, test method:	nzell, phone +49 (0)6659

	If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the
	supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an
	industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It
	should not be construed as offering an approval for any specific use scenario.
Body Protection	Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
Control of environmental exposure	Prevent further leakage or spillage if safe to do so. Do not let product enter drains

Form: liquid

Colour: colourless

No data available

No data available No data available

No data available

materials.

or conditions: oxidizing

11 °C (52 °F) - closed cup

materials.Extremely flammable in the presence of the following materials

#### 9. Physical and chemical properties

Appearance

Odor Odour Threshold pH Melting point/freezing point Initial boiling point and boiling range Flammability (solid, gas) Flash point Evaporation rate Upper/lower flammability or explosive limits Vapour pressure

Vapour density Relative density Water solubility Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Explosive properties Oxidizing properties Other safety information

#### 10. Stability and reactivity

www.rxmarine.com

www.rxmarine.com

**Chemical stability** Possibility of hazardous reactions **Conditions to avoid Incompatible materials** 

Hazardous decomposition products

### 11. Toxicological information

**Information on toxicological effects** 

Acute toxicity

Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity

Reproductive toxicity

Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Additional Information

Stable under recommended storage conditions.

Vapours may form explosive mixture with air. Heat, flames and sparks. Extremes of temperature and direct sunlight. Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents, Chloroformates

In the event of fire: see section 5

www.rxmarine.com

No data available Inhalation: No data available Dermal: No data available IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-(3,6-Dihydroxy-2,4,5,7-tetrabromoxanthen-9-yl)-benzoic acid) ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. No data available **RTECS:** Not available Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Central nervous system - Breathing difficulties - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence (Methanol)

12. Ecological information	www.rxmarine.com
Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
Results of PBT and vPvB assessment	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
Other adverse effects	No data available
13. Disposal considerations	www.rxmarine.com
Waste treatment methods	
Product	Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Contaminated packaging	Dispose of as unused product.
14. Transport information	www.rxmarine.com
DOT (US)	UN number: 1230 Class: 3 Packing group: II
	Proper shipping name: Methanol
	Poison Inhalation Hazard: No
IMDG	UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D
	Proper shipping name: METHANOL

IATA

## 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the<br/>substance or mixtureThis material safety data sheet complies with the requirements of<br/>Regulation (EC) No. 1907/2006.Other regulationsObserve work restrictions regarding maternity protection in accordance to<br/>Dir 92/85/EEC or stricter national regulations where applicable. Take<br/>note of Dir 94/33/EC on the protection of young people at work.Chemical Safety AssessmentFor this product a chemical safety assessment was not carried out

#### 16. Other information

Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and weassume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary

www.rxmarine.com

www.rxmarine.com

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol

damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.