

## 1. Product and Company Identification

www.rxmarine.com

Product Name Antiperspirant and Sweat Marks  
Part Number RXXSOL-15-2701-005

### Company Details:....

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400  
Fax +91 22 27612100 ::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmraine.com](http://www.rxmraine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Based on our hazard evaluation, the following chemical substance(s) in this product have been identified as hazardous.

Ingredient	CAS Number	Percent (w/w)
Isobutane	75-28-5	30 ± 60 %
Aerosol Antiperspirant		
Cyclopentasiloxane	541-02-6, 556-67-2	10 ± 30 %
Aluminum Chlorohydrate	1327-41-9	5 ± 10 %

## 3. Hazards Identification

www.rxmarine.com

### EMERGENCY OVERVIEW

#### CAUTION

This product is a clear to yellowish solution with various scents, in an aerosol can. Direct contact with eyes may cause irritation.

Intentional inhalation of vapors may cause irritation of the nose, throat, and respiratory tract. Breathing high vapor concentrations may produce

anesthetic effects, nausea, dizziness, headache. Intentional misuse of product (i.e., huffing) may produce death. Keep out of reach of children. No significant environmental effects. Dangerous fire hazard when exposed to heat or flame. Product is stable.

This product is labeled in accordance with guidelines set forth in the Food, Drug, and Cosmetic Act. The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable

to this Material Safety Data Sheet may differ from the requirements of the FD&C Act and as a result, this MSDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

#### Regulatory Status

This product is considered to be hazardous under OSHA's Hazard Communication Standard (29 CFR 1900.1200). This MSDS should be retained and available for employees and other users of this product.

Potential Health Effects	
Eye Contact	This product may cause moderate to severe irritation.
Skin Contact	Repeated or prolonged excessive exposure may cause irritation or sensitization dermatitis in previously exposed individuals.
Ingestion	Not an anticipated route of exposure. Nausea and possible vomiting may occur.
Inhalation	Airborne concentrations of isobutane, the propellant in this product, exceeding workplace standards may cause central nervous system effects and irritation of the throat and lungs with coughing, nausea and vomiting. Prolonged exposure may cause dizziness, weakness, peripheral numbness, nervousness, and drowsiness.
Subchronic/Chronic Health Effects	None known.
Medical Conditions Generally Recognized As Being Aggravated By Exposure	Pre-existing respiratory conditions such as asthma.
Potential Environmental Effects	See Section 12: Ecological Information.

## 4. First Aid Measures

[www.rxmarine.com](http://www.rxmarine.com)

Eyes	Immediately rinse eyes with plenty of water, occasionally lifting upper and lower lids, until no evidence of product remains. Get medical attention if pain or irritation persists.
Skin	Rinse affected area with mild soap and water until no evidence of product remains. Discontinue exposure. Get medical attention if irritation develops
Ingestion	Dilution by rinsing the mouth and giving water or milk to drink is generally recommended. Contact physician or local poison control center if any symptoms appear.
Inhalation	Remove from exposure area to fresh air immediately. Keep affected person warm and at rest. Treat symptomatically and supportively. Contact physician or local poison control center. If breathing has stopped, give artificial respiration, and get medical attention immediately.
Note to Physician	The physician's judgment should be used to control symptoms and clinical condition based on the individual reactions of the patient.

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

Flammable Properties	
OSHA Flammability Classification	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.
	In a fire or if heated, a pressure increase will occur and the container may burst, with the
	risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along
	the ground. Vapors may accumulate in low or confined areas or travel a considerable
	distance to a source of ignition and flash back.
	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.
	In a fire or if heated, a pressure increase will occur and the container may burst, with the
	risk of a subsequent explosion. The vapor/gas is heavier than air and will

---

spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Flammable Liquid  Class IA

Not applicable

Not available

**spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if**

**there is a fire. No action shall be taken involving any personal risk or without suitable**

**training. Move containers from fire area if this can be done without risk. Use water**

**spray to keep fire-exposed containers cool.**

Irritating smoke, carbon monoxide, and carbon dioxide.

Auto-Ignition Temperature

Flammable/Explosive limits  lower

Hazardous Combustion Products

Flash Point