

## 1. Product and Company Identification

www.rxmarine.com

Product Name Super Hydro 3X  
Part Number RXSOL-43-4143-210

Blend of Corrosion Inhibitor - Oxygen Scavenger - Biocide

Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400  
Fax +91 22 27612100 ::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)  
Website [www.rxmarine.com](http://www.rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

Product Name	CAS Number	EC Number	Weight Percentage	Classification according to Regulation (EC) No. 1272/2008
Quaternary Ammonium Compounds, C12-C16 Benzyl Alkyldimethyl Chlorides	68424-85-1	939-253-5	10 - 25	H302 H314
Ammonium Hydrogensulphite	10192-30-0	233-469-7	10 - 30	Eye Irrit. 2, H319
2-(Methoxymethylethoxy) Propanol	34590-94-8	252-104-2	1 - 10	Not classified
Methanol	67-56-1	200-659-6	1 - 10	Acute Tox. 4 (Oral), H302

## 3. Hazards Identification

www.rxmarine.com

Classification according to Regulation (EC) No. 1272/2008

Acute toxicity (oral), Category 4 H302

Skin corrosion/irritation, Category 1, Sub-Category 1B H314

Serious eye damage/eye irritation, Category 1 H318

Hazardous to the aquatic environment ☑ Acute Hazard, Category 1 H400

Hazardous to the aquatic environment ☑ Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Label elements

Signal word	Danger
Contains	Ethane-1,2-diol, methanol, Quaternary ammonium compounds, benzyl C12-C16 (even numbered)-alkyldimethyl chlorides
Hazard statements	H302 - Harmful if swallowed.  H314 - Causes severe skin burns and eye damage.  H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements	P264 - Wash hands thoroughly after handling.  P280 - Wear eye protection, protective clothing, protective gloves.  P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.. Immediately call a POISON CENTER or doctor.  P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes.  Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a  POISON CENTER or doctor.  P321 - Specific treatment (see supplemental first aid instruction on this label).  P391 - Collect spillage.
EUH-statements	EUH031 - Contact with acids liberates toxic gas.
Other hazards	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII  This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## 4. First Aid Measures

[www.rxmarine.com](http://www.rxmarine.com)

General	Call a physician immediately.
Inhalation	Remove person to fresh air and keep comfortable for breathing.
Skin contact	Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
Ingestion	Rinse mouth. Do not induce vomiting. Call a physician immediately.
Most important symptoms and effects, both acute and delayed	
Symptoms/effects after skin contact	Burns
Symptoms/effects after eye contact	Serious damage to eyes
Symptoms/effects after ingestion	Burns

## 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.
Special hazards arising from the substance or mixture	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and

Hazardous decomposition products in case of fire  
Advice for firefighters

the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Toxic fumes may be released.

Spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Protection during firefighting

Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

Emergency procedures

Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

Protective equipment

Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Avoid release to the environment

For containment

Collect spillage

Methods for cleaning up

Take up liquid spill into absorbent material

Other information

Dispose of materials or solid residues at an authorized site.

Reference to other sections

For further information refer to section 13.

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

Precautions for safe handling

Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Storage conditions

Store locked up. Store in a well-ventilated place. Keep cool.

Specific end use(s)

No additional information available

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

(2-methoxymethylethoxy)propanol (34590-94-8)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name

(2-Methoxymethylethoxy)-propanol

IOEL TWA

308 mg/m<sup>3</sup>

IOEL TWA [ppm]

50 ppm

Remark

Skin

(2-Methoxymethylethoxy)propanol (34590-94-8)

Regulatory reference

COMMISSION DIRECTIVE 2000/39/EC

United Kingdom - Occupational Exposure Limits

Local name

(2-Methoxymethylethoxy)-propanol

IOEL TWA

308 mg/m<sup>3</sup>

IOEL TWA [ppm] (OEL TWA) [2]

50 ppm

Remark

Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic

Regulatory reference	toxicity) EH40/2005 (Fourth edition, 2020). HSE
Ethane-1,2-diol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	52 mg/m <sup>3</sup>
IOEL TWA [ppm] (OEL TWA) [2]	20 ppm
IOEL STEL	104 mg/m <sup>3</sup>
IOEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> particulate
	52 mg/m <sup>3</sup> vapour
IOEL TWA [ppm] (OEL TWA) [2]	20 ppm vapour
IOEL STEL(OEL STEL)	104 mg/m <sup>3</sup> vapour
WEL STEL (OEL STEL)	40 ppm vapour
WEL STEL (OEL STEL) [ppm]	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Remark	Skin
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Methanol (67-56-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methanol
IOEL TWA	260 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Occupational Exposure Limits	
Local name	Methanol
WEL TWA (OEL TWA) [1]	266 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Recommended monitoring procedures	No additional information available
Air contaminants formed	No additional information available
DNEL and PNEC	No additional information available
Control banding	No additional information available
Exposure controls	
Appropriate engineering controls	

Appropriate engineering controls		Ensure good ventilation of the work station.			
Safety glasses					
Type	Field of application		Characteristics	Standard	
Safety glasses			With side shields	EN 166	
Skin protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Butyl rubber	3 (> 60 minutes)	Nitrile 0.4 mm; 0.7 mm	Butyl	EN ISO 374
Respiratory protection					
Device	Filter type		Condition	Standard	
	Type A - High-boiling (>65 °C) organic compounds, Filter P (white)			EN 143, EN 14387	

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

Physical state	liquid
Colour	Pale yellow.
Odor	Characteristic odour
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability	Not available
Explosive limits	Not available
Lower explosive limit (LEL)	Not available
Upper explosive limit (UEL)	Not available
Flash point	60 – 93 °C
Auto-ignition temperature	Not available
Decomposition temperature	Not available
pH	4 – 6
Viscosity, kinematic	Not available
Viscosity, dynamic	< 10 cP 20 °C, S-18 Spindle, 100 RPM
Solubility	Not available
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50 °C	Not available
Density	Not available
Relative density	Not available
Relative vapour density at 20 °C	Not available
Particle size	Not applicable
Particle size distribution	Not applicable
Particle shape	Not applicable
Particle aspect ratio	Not applicable
Particle aggregation state	Not applicable
Particle agglomeration state	Not applicable
Particle specific surface area	Not applicable

Particle dustiness	Not applicable
Information with regard to physical hazard classes	No additional information available
Other safety characteristics	No additional information available

## 10. Stability and reactivity

www.rxmarine.com

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Contact with acids liberates toxic gas.
Conditions to avoid	None under recommended storage and handling conditions (see section 7).
Incompatible materials	Acids
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

www.rxmarine.com

Acute toxicity (oral)	Harmful if swallowed.
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
SUPER HYDRO 3X	
ATE CLP (oral)	
Ammonium Hydrogensulphite (10192-30-0)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.5 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
(2-methoxymethylethoxy)propanol (34590-94-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 3000 mg/m <sup>3</sup> Source: ECHA
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 dermal	3500 mg/kg bodyweight Animal: mouse
LC50 Inhalation - Rat	2500 mg/m
Methanol (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg bodyweight Animal: rat
LD50 dermal	17100 mg/kg bodyweight
LC50 Inhalation - Rat	43700 mg/m <sup>3</sup>
Quaternary Ammonium Compounds, Benzyl C12-C16 (even numbered)-alkyldimethyl chlorides (68424-85-1)	
LD50 oral rat	795 mg/kg bodyweight
LD50 dermal rabbit	3412.5 mg/kg bodyweight
LC50 Inhalation - Rat	0.22 - 0.28 mg/l/4h

Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	pH: 4 - 6. Causes severe skin burns.
Respiratory or skin sensitisation	pH: 4 - 6 Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Ethane-1,2-diol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Reproductive toxicity	Not classified
methanol (67-56-1)	
NOAEL (animal/male, F0/P)	