

1. Product and Company Identification

www.rxmarine.com

Product Name Coagulant for Cooling Water System RXSOL-43-4095-025 25 Kg. PWD
Product Type RXSOL-43-4095-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 27815540 / 41 / 42
Fax +91 22 2781 1318 :::AOH :0091 9322594669
Email mail@rxmarine.com

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Visakhapatnam, Fujairah, Muscat

2. Composition / Information on ingredients

www.rxmarine.com

Components	CAS Number	Proportion	Hazard Codes
Polyaluminium Chloride	7-41-9	100%	H302 H315 H319

3. Hazards Identification

www.rxmarine.com

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: WARNING

Subclasses:

Subclass 6.1 Category D Substances which are acutely toxic.
Subclass 6.3 Category A Substances that are irritating to the skin.
Subclass 6.4 Category A Substances that are irritating to the eye.

Hazard Statement(s):

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.
P103 Read label before use
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection

Response:

P301+P312 IF SWALLOWED Call a POISON CENTER or doctor/physician if you feel unwell.
P330 Rinse mouth.

P302+P352 IF ON SKIN	Wash with plenty of soap and water.
P321	Specific treatment (see First Aid Measures on the Safety Data Sheet).
P332+P313 If skin irritation occurs	Get medical advice/attention.
P362	Take off contaminated clothing before re-use.
P305+P351+P338 IF IN EYES	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists	Get medical advice/attention.

Storage:
No storage statements.

Disposal:
P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

4. First Aid Measures

www.rxmarine.com

Inhalation	Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
Skin Contact	If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.
Eye Contact	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.
Ingestion	Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:
Treat symptomatically.

5. Fire-fighting Measures

www.rxmarine.com

Suitable Extinguishing Media:
Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the substance or mixture:
Non-combustible material.

Special protective equipment and precautions for fire-fighters:
Decomposes on heating emitting toxic fumes, including those of aluminium oxide, and hydrogen chloride. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. Accidental Release Measures

www.rxmarine.com

Emergency procedures/Environmental precautions:
Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:
Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling:

Avoid skin and eye contact and breathing in dust. Avoid handling which leads to dust formation.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Protect from moisture. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

8. Exposure controls and personal protection

www.rxmarine.com

Workplace Exposure Standards:

No value assigned for this specific material by the New Zealand Department of Labour (Health & Safety). However, Workplace Exposure Standard(s) for constituent(s):

Aluminium, as Al: Soluble salts WES-TWA 5 mg/m³

As published by the New Zealand Department of Labour (Health & Safety).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Avoid generating and breathing in dusts. Use with local exhaust ventilation or while wearing dust mask. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Orica Personal Protection Guide No. 1, 1998: F - OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, DUST MASK.

Wear overalls, chemical goggles and impervious gloves. Avoid generating and inhaling dusts. If dust exists, wear dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

www.rxmarine.com

Information on basic physical and chemical properties:

Physical state	Powder
Colour	Pale Yellow
Odour	Mild
Solubility	Soluble in water.
Specific Gravity	0.85 +/-0.05 (Bulk density)
Relative Vapour Density (air=1)	Not available
Vapour Pressure (20 °C)	Not available
Flash Point (°C):	Not available
Autoignition Temperature (°C):	Not available
Flammability Limits (%):	Not available
Melting Point/Range (°C):	Not available
pH	3.5 - 5.0 (Al ₂ O ₃ 0.3% w/v solution)

10. Stability and reactivity

www.rxmarine.com

Reactivity	Reacts with chlorates. Reacts with chlorites.
Chemical stability:	Hygroscopic: absorbs moisture or water from surrounding air.
Possibility of hazardous reactions	None known.
Conditions to avoid	Avoid exposure to moisture.
Incompatible materials	Incompatible with chlorates , chlorites .
Hazardous decomposition products:	Hydrogen chloride.

11. Toxicological information

www.rxmarine.com

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion	Swallowing can result in nausea, vomiting, diarrhoea, and abdominal pain.
Eye contact	An eye irritant.
Skin contact	Contact with skin will result in irritation.
Inhalation	Material may be irritant to the mucous membranes of the respiratory tract (airways).
Acute toxicity	Oral LD50 (rat): 681 mg/kg. Oral LD50 (mice): 316 mg/kg.
Chronic effects	No information available for the product.

12. Ecological information

www.rxmarine.com

Ecotoxicity
Avoid contaminating waterways.

13. Disposal considerations

www.rxmarine.com

Disposal Methods:
Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. Transport information

www.rxmarine.com

Road and Rail Transport	Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.
Marine Transport	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.
Air Transport	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. Regulatory information

www.rxmarine.com

Classification:
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.
Subclasses:

Subclass 6.1 Category D	Substances which are acutely toxic.
-------------------------	-------------------------------------

Subclass 6.3 C

Substances that are irritating to the skin.

Category A

Subclass 6.4 Category A

Substances that are irritating to the eye.

Hazard Statement(s):

H302

Harmful if swallowed

H315

Causes skin irritation.

H319

Causes serious eye irritation.

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:- R34: Causes burns; R36: Irritating to eyes; R37: Irritating to respiratory system; R41: Risk of serious damage to eyes. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.