

1. Product and Company Identification

www.rxmarine.com

Product Name Polypropylene Glycol 2000
Part Number RXSOL-96-1949-200

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmraine.com

2. Composition / Information on ingredients

www.rxmarine.com

Substances

Formula $C_3H_8O_2$
CAS-No 25322-69-4
EC-No. 500-039-8

No components need to be disclosed according to the applicable regulations.

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Label elements Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008
Other hazards None

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

If inhaled If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact Wash off with soap and plenty of water.

In case of eye contact Flush eyes with water as a precaution.

If swallowed Never give anything by mouth to an unconscious person. Rinse mouth with water

Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed No data available

Extinguishing media

Suitable extinguishing media

Special hazards arising from the substance or mixture

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Carbon oxides

Advice for firefighters

Further information

Wear self-contained breathing apparatus for firefighting if necessary

No data available

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapors, mist or gas.

Environmental precautions

For personal protection see section 8

Methods and materials for containment and cleaning up

Do not let product enter drains.

Reference to other sections

Keep in suitable, closed containers for disposal.

For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Recommended storage temperature see product label.

Recommended storage temperature see product label. Tightly closed.

Specific end use(s)

Recommended storage temperature see product label.

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Ingredients with workplace control parameters

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet,

supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet,

supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following

standards: DIN EN 143, DIN 14387 and other accompanying standards relating to

the used respiratory protection system.

Recommended Filter type: Filter type P1

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory

protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Do not let product enter drains..

Respiratory protection

Control of environmental exposure

9. Physical and chemical properties

www.rxmarine.com

Information on basic physical and chemical properties

Appearance

Form: Liquid

Odor

No data available

Odor Threshold

No data available

pH

No data available

Melting point/freezing point

Melting point/range: < -150 °C - OECD Test Guideline 102

Initial boiling point and boiling range

287,6 °C - OECD Test Guideline 103

Flash point	229,44 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	No data available
Vapor pressure	