

1. Product and Company Identification

www.rxmarine.com

Product Name Silica Gel 2 Gram
Part Number RXSOL-96-6014-002

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmraine.com

2. Composition / Information on ingredients

www.rxmarine.com

Substance

Formula SiO₂
CAS-No. 112926-00-8
EC-No. 231-545-4

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Label elements Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

If inhaled After inhalation: fresh air.

In case of skin contact In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed No data available

5. Fire-fighting Measures

www.rxmarine.com

Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard.

In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along

the ground. Vapors may accumulate in low or confined areas or travel a considerable

distance to a source of ignition and flash back.

silicon oxides

Not combustible.

Ambient fire may liberate hazardous vapours.

Advice for firefighters

In the event of fire, wear self-contained breathing apparatus

Further information

Suppress (knock down) gases/vapors/mists with a water spray jet.

spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8

Environmental precautions

No special precautionary measures necessary.

Methods and materials for containment and cleaning up

Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

Reference to other sections

For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet,

supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Required when dusts are generated.

Respiratory protection

Our recommendations on filtering respiratory protection are based on the following

standards: DIN EN 143, DIN 14387 and other accompanying standards relating to

the used respiratory protection system.

Recommended Filter type: Filter type P1

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory

protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

No special precautionary measures necessary

Control of environmental exposure

9. Physical and chemical properties

www.rxmarine.com

Appearance

Physical state

Liquid. [COLORLESS LIQUID]

Colour

Colorless

Odor

Characteristic.

Odor Threshold

Not available.

pH

Not available.

Melting Point