

| | |
|--------------|-------------------|
| Product Name | RXSOL-19-1566-210 |
| Product Type | Hexane |

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999 / 27815540 Fax +91 22 2781 1318 ::AOH :0091 9821214367 Email
mail@rxmarine.com Website www.rxmarine.com

Chemical Name

CAS Number

EC Number

Index number

n-hexane

110-54-3

203-777-6

601-037-00-0

Hazard description:

Information concerning particular hazards for human and environment:

R 11 Highly flammable.

R 38 Irritating to skin.

R 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R 62 Possible risk of impaired fertility.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

General information Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water.

After swallowing

If symptoms persist consult doctor.

Suitable extinguishing agents:

For safety reasons unsuitable extinguishing agents: Water with full jet

Protective equipment: No special measures required.

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting: Dilute with plenty of water. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Handling:**Information for safe handling:**

Protect from ignition. Wear protective clothing and use approved respirator equipment. Absorb spilled material in an absorbent recommended for solvent spills and remove to a safe location for disposal by approved methods. If released to the environment, comply with all regulatory notification requirements.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

110-54-3 n-hexane

PEL (USA)

REL (USA)
TLV (USA)
WEL (Great Britain)

1800 mg/m³, 500 ppm
180 mg/m³, 50 ppm
176 mg/m³, 50 ppm
Skin; BEI
72 mg/m³, 20 ppm
72 mg/m³, 20 ppm

Additional information: The lists valid during the making were used as basis.

Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves: The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

General Information

Form

Fluid

Colour

Colourless

Odour

Characteristic

Change in condition

Melting point/Melting range

-95°C

Boiling point/Boiling range

69°C

Flash point

-26°C

Ignition temperature 240°C

Danger of explosion

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

| | | | | | | |
|--------------------------|------------------------|--|-------|-----------|-------------------------|---------|
| Explosion limits: | Lower | 1.2 Vol % | Upper | 7.4 Vol % | Vapour pressure at 20°C | 160 hPa |
| Density at 20°C | 0.66 g/cm ³ | Solubility in / Miscibility with water at 20°C | | 0.1 g/l | | |

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Dangerous reactions No dangerous reactions known.

Dangerous decomposition products: No dangerous decomposition products known.

Acute toxicity: Primary irritant effect: on the skin Irritant to skin and mucous membranes. on the eye No
irritating effect. Sensitization No sensitizing effects known.

Ecotoxical effects:

Remark: Toxic for fish

General notes: Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

Product:

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging: Recommendation: Disposal must be made according to official regulations.

| Land transport ADR/RID (cross-border) | | | | ADR/RID class | | 3 Flammable liquids. | | Danger code (Kemler) | | | | |
|---------------------------------------|-----------|---|----------------------|-----------------|--------------|----------------------|-------------------------|----------------------|----|---------------------------|------------|------------------|
| 33 | UN-Number | | 1208 | Packaging group | | II | Hazard label | | 3 | Special marking | | |
| Symbol (fish and tree) | | | Description of goods | | 1208 HEXANES | | Maritime transport IMDG | | | | IMDG Class | |
| 3 | UN Number | | 1208 | Label | | 3 | Packaging group | | II | EMS Number | | |
| F-E,S-D | | Marine pollutant | | No | | Proper shipping name | | HEXANES | | Air transport ICAO-TI and | | |
| ATA-DGR | | ICAO/IATA Class | | 3 | | UN/ID Number | | 1208 | | Special marking | | Symbol (fish and |
| tree) | | Label | | 3 | | Packaging group | | II | | Proper shipping name | | HEXANES |
| Environmental hazards | | Environmentally hazardous substance, liquid; Marine Pollutant | | | | | | | | | | |

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Risk phrases:

11 Highly flammable.

38 Irritating to skin.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

62 Possible risk of impaired fertility.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

29 Do not empty into drains.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.